

06/23/00  
1c816 U.S. PTO

069620

A

Please type a plus sign (+) inside this box → ☒

PTO/SB/05 (1/98)  
Approved for use through 09/30/2000. OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	BK-020-04
	First Inventor or Application Identifier	H. Brock Kolls
	Title	An Internet Based Network For Automotive Applications Including The Facilitation Of E-Commerce And E-Business, And Management Of Wireless Connectivity With Vehicles
	Express Mail Label No.	EK865241095US

<b>APPLICATION ELEMENTS</b> See MPEP chapter 600 concerning utility patent application contents.	<b>ADDRESS TO:</b> Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original, and a duplicate for fee processing)	6. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 134] (preferred arrangement set forth below) <ul style="list-style-type: none"><li>- Descriptive title of the Invention</li><li>- Cross References to Related Applications</li><li>- Statement Regarding Fed sponsored R &amp; D</li><li>- Reference to Microfiche Appendix</li><li>- Background of the Invention</li><li>- Brief Summary of the Invention</li><li>- Brief Description of the Drawings (if filed)</li><li>- Detailed Description</li><li>- Claim(s)</li><li>- Abstract of the Disclosure</li></ul>	7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ul style="list-style-type: none"><li>a. <input type="checkbox"/> Computer Readable Copy</li><li>b. <input type="checkbox"/> Paper Copy (identical to computer copy)</li><li>c. <input type="checkbox"/> Statement verifying identity of above copies</li></ul>
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 32]	
4. Oath or Declaration [Total Pages 2] <ul style="list-style-type: none"><li>a. <input checked="" type="checkbox"/> Newly executed (original or copy)</li><li>b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below]<ul style="list-style-type: none"><li>i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).</li></ul></li></ul>	
5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	
<b>ACCOMPANYING APPLICATION PARTS</b>	
8. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))	
9. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement <input type="checkbox"/> Power of Attorney (when there is an assignee)	
10. <input type="checkbox"/> English Translation Document (if applicable)	
11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations	
12. <input type="checkbox"/> Preliminary Amendment	
13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) <ul style="list-style-type: none"><li>* Small Entity <input type="checkbox"/> Statement filed in prior application, Status still proper and desired (P03/REV1)</li></ul>	
14. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)	
15. <input type="checkbox"/> Other: .....	
16. <input type="checkbox"/> Other: .....	
* A new statement is required to be entitled to pay small entity fees, except where one has been filed in a prior application and is being relied upon.	

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

<input type="checkbox"/> Continuation	<input type="checkbox"/> Divisional	<input checked="" type="checkbox"/> Continuation-in-part (CIP)	of prior application No: 09/593881
Prior application information: Examiner		Group / Art Unit:	

<b>18. CORRESPONDENCE ADDRESS</b>					
<input type="checkbox"/> Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or <input checked="" type="checkbox"/> Correspondence address below					
Name	H. Brock Kolls				
Address	1573 Potter Drive				
City	Pottstown	State	PA	Zip Code	19464
Country	United States	Telephone	610-705-3371	Fax	610-705-3371

Name (Print/Type)	H. Brock Kolls	Registration No. (Attorney/Agent)	#42,757
Signature	<i>H. Brock Kolls</i>	Date	6/23/00

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Docket No.  
**BK-020-04**

Filing Date  
**June 23, 2000**

Issue Date

**Invention: An Internet Based Network For Automotive Applications Including The Facilitation Of E-Commerce And E-Business, And Management Of Wireless Connectivity With Vehicles**

☒ the specification to be filed herewith.  
☐ the application identified above.  
☐ the patent identified above.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern or organization exists.
- ☐ Each such person, concern or organization is listed below.

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 CFR 1.27)

ADDRESS

☐ Individual      ☐ Small Business Concern      ☐ Nonprofit Organization

ADDRESS

☐ Individual      ☐ Small Business Concern      ☐ Nonprofit Organization

ADDRESS

☐ Individual      ☐ Small Business Concern      ☐ Nonprofit Organization

ADDRESS

☐ Individual      ☐ Small Business Concern      ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR H. Brock Kolls

SIGNATURE OF INVENTOR HBH

DATE: 6/23/00

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

This U.S. non-provisional application is a continuation in part application that claims priority of a U.S. non-provisional application, Serial No. 09/593881, inventor H. Brock Kolls, entitled A COMMUNICATION INTERFACE DEVICE FOR MANAGING WIRELESS DATA TRANSMISSION BETWEEN A VEHICLE AND THE INTERNET, filed June 14, 2000, which is a continuation in part application that claims priority of a U.S. non-provisional application, Serial No. 09/579263, inventor H. Brock Kolls, entitled COMMUNICATING INTERACTIVE DIGITAL CONTENT BETWEEN VEHICLES AND INTERNET BASED DATA PROCESSING RESOURCES FOR THE PURPOSE OF TRANSACTING E-COMMERCE OR E-BUSINESS, filed May 25, 2000; which is a continuation in part application that claims priority of a U.S. non-provisional application, Serial No. 09/564471, inventor H. Brock Kolls, entitled TRANSACTING E-COMMERCE AND CONDUCTING E-BUSINESS RELATED TO IDENTIFYING AND PROCURING AUTOMOTIVE SERVICE AND VEHICLE REPLACEMENT PARTS, filed May 3, 2000; which is a continuation in part application that claims priority of a U.S. non-provisional application, Serial No. 09/556543, inventor H. Brock Kolls, entitled AN IN VEHICLE DEVICE FOR WIRELESSLY CONNECTING A VEHICLE TO THE INTERNET AND FOR TRANSACTING E-COMMERCE AND E-BUSINESS, filed April 24, 2000.

### TECHNICAL FIELD OF THE INVENTION

The present invention relates to system for wirelessly data communicating between and effectuating a network with a plurality of vehicles and a plurality of data processing resources, including Internet based data processing resources. Such wireless data communications can include data communicating vehicle information, remote monitoring of engine and vehicle performance, data communicating Internet based content, transacting e-mail, e-commerce, and e-business, and adjusting or controlling vehicle operation. Remote monitoring, adjustment, and control of vehicle operation can be effectuated by way of an Internet based data processing resource and can include monitoring vehicle telemetry and metric data. Vehicle telemetry and metric data can include global positioning system (GPS) data and engine performance data.

### BACKGROUND OF THE INVENTION

Vehicles, including trucks and automobiles have become increasingly more complex with the advent of engine control systems. These engine control systems can exhibit the ability to diagnose, record, monitor, control, and or optimize engine performance. In addition, some engine control systems may offer additional functionality in the form of vehicle security alarms, door locking, ignition enabling, radio control, or other vehicle command and control functionality.

Even with the advances in engine control systems it can still be difficult for anyone but a mechanic with special diagnostic equipment to obtain and view the engine performance data and or other engine control system settings. In addition, such engine control system data may only be accessible from a collision, repair or service center location and can not typically be monitored, viewed, or altered while the vehicle is in motion or in operation on the open roadway.

The inability to access and analyze engine performance data while a vehicle is in motion or in operation on an open roadway can prevent accurate engine performance analysis and or part failure prediction. Accurate part failure prediction can be  
5 characterized as the ability to predict part or system degradation or failure based on engine telemetry data and other vehicle operational data before degradation or failure of the part or system occurs.

The inability to accurately predict when engine problems may arise can cause the  
10 vehicle to become disabled while in between a point of origin and a desired destination. When a vehicle becomes disabled before reaching a desired destination the user of the vehicle and other occupants in the vehicle can find themselves stranded. Once stranded the user and occupants of the disabled vehicle may not know where or who to call for help, service, or for vehicle repairs. In addition, the inability to diagnose and repair even  
15 the simplest of vehicle problems on the side of a roadway can result in travel delays and expense in towing the vehicle to a collision, repair site or service center location where repairs to the vehicle can be effectuated.

As more and more people take to the roadways in their vehicles for travel the  
20 chance of being stranded in unfamiliar areas increases. As the chance of becoming stranded in an unfamiliar area increases the need to be able to rapidly locate auto part stores, collision centers, service centers, and emergency services can also increase.

Recently, Internet based auto part and information companies such as  
25 WRENCHHEAD.COM, PARTS.COM, CARPARTS.COM, SPORTWING.COM, CARPARTSONSALE.COM, NAPAONLINE.COM, PARTSAMERICA.COM, CSKAUTO.COM, ALLDATA.COM, MECHANICNET.COM, and others have begun providing online part locating and ordering services. These virtual online auto part web

sites or portals can be convenient to visit and use from the comfort of one's own home personal computer (PC) or office PC, but can be difficult to utilize when stranded on the side of a road, or when stranded in an unfamiliar area.

5           Auto part stores with physical store locations such as CAR QUEST, AUTOZONE, ADVANCE AUTO PARTS, CHIEF AUTO PARTS, DISCOUNT AUTO PARTS, PEP BOYS, NAPA, MOPAR AUTO PARTS, CSK AUTO (including  
10           CHECKER AUTO PARTS, SCHUCK'S AUTO SUPPLY, and KRAGEN AUTO PARTS), and others have long maintained in-store databases where customers can look up replacement parts. Physical auto part stores can be convenient when the required parts are in stock and a person has the means and time to visit such a location. However, such locations can have little to offer and can be difficult to utilize when stranded on the side of a road, or when stranded in an unfamiliar area.

15           Another issue with virtual online stores and physical auto part stores can be that a customer may not be skilled in the art of vehicle repair or may not have access to pertinent vehicle information necessary for the correct selection of a replacement part. In addition, auto part stores can find themselves in the awkward position of having to dispense advice and help customers with access to limited vehicle knowledge or  
20           incomplete information. Specific to the virtual online stores the lack of immediate access to the vehicle can prevent even the friendliest of customer service departments from aiding the customer in ascertaining a correct and accurate diagnosis of a vehicle problem or dispensing timely repair and part selection advice. In the case of physical auto part stores an employee can lack the resources or time to aid a customer in diagnosing vehicle  
25           problems. Even in a case where an online customer service department, or an employee tries to assist a customer in diagnosing a vehicle problem the lack of easily obtainable engine performance data or other vehicle operational data could prevent a correct and accurate diagnosis.

5

15

25

The inability of online virtual auto part web sites or portal stores, physical auto part stores, and vehicle manufacturers to monitor engine performance data can result in lost sales and lost business opportunities. Lost sales and business opportunities can occur as a result of not anticipating service needs, or accurately diagnosing engine problems. Lost business opportunities can also result from the inability to uniquely identify a vehicle and or the vehicle's owner. Such unique identification could enable targeted marketing opportunities based on immediate and future vehicle service needs.



Online virtual auto part web sites or portal stores, physical auto part stores, and vehicle manufacturers can also lose sales and business opportunities by not maximizing Internet related business opportunities. Internet related business opportunities have allowed a wide variety of traditional businesses and services that support the auto industry to move their business products and service offerings online and create virtual companies. Examples can include advertising services, maps service, hotel and motel directories, radio stations, television stations, and news organizations to name a few.

A number of deficiencies give rise to the long felt need of the present invention. Such deficiencies can include the inability to data communicate telemetry data and stored system data within a vehicle's engine control system to the Internet and or Internet based data processing resources. In addition, the inability of auto part retailers and vehicle manufacturers to dynamically tie inventory and part databases to real time vehicle telemetry and metric data can result in lost sales and lost business opportunities.

Other deficiencies can include the inability of online and physical auto part stores to augment there existing part databases, and data processing resources. Such auto part store databases and data processing resource deficiencies can include a lack of support for monitoring and evaluating vehicle engine performance data and other vehicle data, the inability to use engine performance data to aid customers in accurately diagnosing vehicle problems, and selecting correct replacement parts.

Other deficiencies can include the inability to remotely anticipate vehicle and customer service needs, and vehicle requirements based in part on vehicle telemetry and metric data. Furthermore, the inability to uniquely identify and data communicate with a specific vehicle can prevent or limit customer support and other business opportunities.

### SUMMARY OF THE INVENTION

00602971.06300  
The present invention relates to an in-vehicle device for remotely monitoring vehicle performance, for data communicating Internet based content, and for controlling vehicle operation. An in-vehicle device can be referred to as an in-vehicle device 200. Remote monitoring and control of vehicle operation can be by way of an Internet based data processing resource and can include vehicle telemetry and metric data. Vehicle telemetry and metric data can include global positioning system (GPS) data, vehicle operational data, engine performance data, and other vehicle data. Such an in-vehicle device 200 can wirelessly data communicate over the Internet to Internet based data processing resources, and to other data processing resources.

The present invention also relates to a communication interface device for data communicating wirelessly with an in-vehicle device 200. A communication interface device can be referred to as a COM device 100. A COM device 100 can data communicate wirelessly to an in-vehicle device 200, and simultaneously data communicate wired or wirelessly over the Internet to Internet based data processing resources, and to other data processing resources.

20 The present invention also relates to an Internet appliance for data communicating wirelessly with an in-vehicle device 200. An Internet appliance can be referred to as an Internet appliance 322. An Internet appliance 322 can data communicate wirelessly to an in-vehicle device 200, and simultaneously data communicate wired or wirelessly over the Internet to Internet based data processing resources, and to other data processing  
25 resources.

The present invention also relates to an Internet based network architecture for data communicating between Internet based data processing resources and a plurality of

vehicles each equipped an in-vehicle device 200. Data communication between data processing resources and an in-vehicle device 200 can be by way of a direct data communication between the data processing resource and an in-vehicle device 200. Alternatively, data communication between the data processing resource and an in-vehicle device 200 can be by way of a data communication facilitated by a COM device 100, or an Internet appliance 322.

The present invention also relates to the system formed by the corporation of a plurality of COM device 100, a plurality of in-vehicle device 200, the network to manage the devices and the data processing resources utilized by both devices. Such a system can be utilized to transact and conduct a wide variety and types of e-commerce and e-business.

#### **BRIEF DESCRIPTION OF FIGURES**

The present invention is best understood from the following detailed description when read in connection with the accompanying drawings. Included in the drawings are the following Figures:

Figure 1A shows a personal computer workstation;

Figures 1B-1J shows a plurality of communication interfacing device 100 and a plurality of in-vehicle device 200 physical locations and device configurations;

Figure 1K shows a communication network including a personal data assistant;

Figure 1L shows a communication network including a wireless phone;

Figure 1M shows a communication network including a pager;

Figure 1N shows a programmable storage device;

Figure 1P shows a store display equipped with a communication interface device 100;

Figures 2A-2C show a data communication network diagram;

10 Figure 3 shows a communication interfacing device 100 block diagram;

Figure 4 shows an in-vehicle device 200 block diagram;

Figure 5 shows a radio interactive digital content, and advertising content server routine 400 flowchart;

Figure 6 shows an Internet based remote control vehicle alarm routine 500 flowchart;

Figure 7 shows an Internet based voice and data communication routine 600 flowchart;

Figures 8A-8B show an Internet based vehicle alarm routine 700 flowchart;

25 Figure 9 shows an Internet based notification routine 800 flowchart;

Figure 10 shows an Internet based information acquisition routine 900 flowchart;

Figure 11 shows an Internet based command and control routine 1000 flowchart;

Figure 12 shows an Internet based interactive digital content, and advertising server routine 1100 flowchart;

5

Figure 13 shows a selection of digital informational content based in part on global positioning system telemetry data routine 1200 flowchart;

Figure 14 shows an Internet based vehicle tracking routine 1300 flowchart;

10

Figures 15A-15B show a vehicle maintenance routine 1400 flowchart;

Figure 16 shows an e-mail, facsimile, and personal data assistant communication routine 1500 flowchart;

15

Figure 17 shows an Internet based remote vehicle diagnostic routine 1600 flowchart;

Figure 18 shows an Internet based audio and video server routine 1700 flowchart;

20

Figure 19 shows an Internet based vehicle audio and videoconferencing routine 1800 flowchart;

Figure 20 shows an online part ordering and delivery routine 1900 flowchart;

25

Figure 21 shows a biometric authorization routine 2000 flowchart; and

Figure 22 shows a vehicle tracking and location routine 2100 flowchart.

### DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1A there is shown a personal computer (PC) system  
5 310 interconnected with a communication interfacing device 100. The PC 310 is  
interconnected with several peripheral devices including a monitor 344, a mouse  
346, and a keyboard 348. Other peripheral devices (not shown) can be  
interconnected with a PC 310. Other peripheral devices can include printers,  
scanners, modems, point of sale (POS) equipment such as bar code readers, as  
10 well as other PC 310 compatible peripheral devices. A PC 310 can be an industry  
standard INTEL x86, CELERON, or Pentium compatible processor or an AMD  
x86 compatible or ATHLON processor based system. In addition, a PC 310 can  
be an APPLE based system. PC's manufactured by DELL, GATEWAY, IBM,  
APPLE, or similar architectures can be a PC 310. A PC 310 can also take the  
15 form of a laptop, notebook, or personal data assistant (PDA).

Figures 1B-1J show a plurality of a stationary communication interface  
device 100 and a mobile in-vehicle device 200. A communication interface device  
100 can be referred to as a COM device 100. A mobile in-vehicle device 200 can  
20 be referred to as an in-vehicle device 200. A COM device 100 and an in-vehicle  
device 200 can be located in any suitable configuration such that the two devices  
can data communicate wirelessly. As such, COM device 100 can be located in a  
plurality of physical locations where, in the normal course of vehicle usage (i.e.  
driving), the two devices could continuously or from time to time be in wireless  
25 proximity with each other. Figure 3 and accompanying disclosure detail the  
functionality and operation of a COM device 100. Figure 4 and accompanying  
disclosure detail the functionality and operation of an in-vehicle device 200.

In general, a COM device 100, and an in-vehicle device 200 can access or be accessed by an Internet based server or an Internet based application server. In addition, a COM device 100, and an in-vehicle device 200 cooperated together and can be referred to as a system. Such a system can include additional local and Internet based data processing resources accessible by the COM device 100, or the in-vehicle device 200. Furthermore, such a system can be utilized to effectuate numerous forms and types of e-commerce and e-business.

E-commerce is the electronic buying and selling of good and services typically conducted over a global network. E-business is the electronic transacting of business over a global network. The Internet can be referred to as a global network.

Referring to Figure 1B there is shown, within a garage, a plurality of COM device 100 embodiments. A COM device 100 can be mounted mutually exclusive from any other device or can be manufactured into other devices.

In an exemplary embodiment a COM device 100 can cache data communicated to it by an Internet based data processing resource or an in-vehicle device 200. In such as embodiment the COM device 100 can receive and cache data until such time the appropriate data processing resource or in-vehicle device 200 becomes available. The ability to cache data can allow a COM device 100 to hold data at a plurality of COM device 100 locations until the appropriate time or until the desired in-vehicle device 200 comes into wireless data communicating proximity. As an example and not limitation, an Internet based data processing resource could initiate a command to stop a vehicle equipped with an in-vehicle device 200. Such a command can be cached in a plurality of COM device 100 until such time the desired in-vehicle 200 comes into wireless data

communication proximity. At such time the command can be data communicated. And the vehicle stopped. The results can then be data communicated to the appropriate Internet based data processing resource as required.

5           The Internet can be referred to as a global network and such terms can be utilized interchangeably with the same scope and meaning in this disclosure. Data processing resources with data connectivity to the Internet can be interchangeably referred to as Internet based data processing resources or global network based data processing resources.

10

A COM device 100 can be referred to as a client, an Internet based data processing resources, or a global network based data processing resource. In addition, an in-vehicle device 200 can be referred to as a client, an Internet based data processing resources, or a global network based data processing resource.

15                   An Internet appliance, such as Internet appliance 322 can be referred to as a global network appliance or global network appliance 322. An Internet appliance 322 can be a COM device 100 or can include a COM device 100 as part of the Internet appliance 322 embodiment.

Internet based data processing resources can include Internet based servers, Internet based appliances, and other Internet based data processing resources. An Internet based server can be referred to as a global network server. Internet based data processing resources can be referred to as global network based data processing resources.

Furthermore, an in-vehicle device 200 and a COM device 100 can be constructed with numerous processor technologies platforms including INTEL



x86 or PENTIUM processor technology, or MOTOROLA processor technologies, such as POWERPC, and the 68HC series of microprocessors and microcontrollers. In addition, an in-vehicle device 200 and a COM device 100 can operate on an embedded binary input-output system (BIOS) including a PC style BIOS and can run embedded system operating systems. Embedded system operating systems (OS) can include OSEK, OSEK/VDX, PALM OS, WINDOWS CE, QNX NEUTRINO, and other embedded system operating systems. In addition, development tools and application software can include MICROSOFT VISUAL STUDIO development tools and application software, VIRTUAL JAVA MACHINE development tools and application software, and other development tools and application software.

A COM device 100 can be interconnected with a parking proximity sensor 300. Furthermore, a COM device 100 can be interconnected with a proximity sensing parking light 354.

In general, a COM device 100 can be built into any suitable device. In this fashion a manufacturer of devices intended for use with vehicles or in convenient proximity to a vehicle can build the functionality of a COM device 100 into their device or product.

An in-vehicle device 200 can be interconnected with a vehicle 314. The portion of vehicle 314 where the driver, passengers, or other occupants are seated can be referred to as the vehicle 314 passenger compartment area 366. An in-vehicle device 200 can have further interconnection to a vehicle's control system, engine control system, or other vehicle operational point as shown in Figure 4.

In-vehicle device 200 can be mounted in any convenient location. Preferable an in-vehicle device 200 can be mounted in a secure location such as under the hood, in a window, or in the truck. Alternatively, an in-vehicle device 200 can be mounted within the vehicle's battery, or in a battery case and can  
5 utilize a secure power connection to the battery as well as be sealed into a clean environment. Replacement of an in-vehicle device 200 can be by way of replacing the vehicle's battery or detaching the in-vehicle device 200 from the battery's enclosure.

10 Referring to Figure 1C there is shown a COM device 100 interconnected with a garage door opener 302. Interconnected with a garage door opener 302 can be a garage door 342. An in-vehicle device 200 interconnected with a vehicle 314 is shown in close proximity to a COM device 100. A garage door opener 302 can be a SEARS, GENIE, STANLEY or similar type of garage door device.

15 Referring to Figure 1D there is shown a COM device 100 interconnect with a gas pump 304. A gas pump 304 can be a similar in type or manufacture to those utilized at most gas stations. A gas pump 304 can include those gas pumps utilized by BP AMOCO, ARCO, SHELL, CHEVRON, MOBIL, TEXACO,  
20 GULF, CONOCO, EXXON, independent station owners, convenience store operators, and other similar types of gas pumps. A COM device 100 can interface to a gas pump point-of-sale terminal. A gas pump point-of-sale terminal can be a WAYNE DRESSAR, GILBARCO, DAYNL, or other similar gas pump point-of-sale terminal.

25 Referring to Figure 1E there is shown a COM device 100 interconnected with a tollbooth 306. A tollbooth 306 can be commonly found on turnpikes, at bridge crossings, and tunnel entrances. In general, a tollbooth 306 can be

established for the purpose of collecting money from a vehicle at certain roadway points, and for the use of certain roadways or passageways. Also shown is a COM device 100 interconnected with a wireless toll-pass system 308. A wireless toll-pass system can be utilized to identify a vehicle and charge a vehicle's owner account for passing through the toll area. A wireless toll-pass system 308 can be an E-ZPASS system, or other similar wireless toll-pass system.

In this embodiment while the vehicle is stopped or slowed at a tollbooth 306 or a wireless toll-pass system 308 an in-vehicle device 200 embodied in a vehicle 314 can data communicate with a COM device 100.

Referring to Figure 1F there is shown a COM device 100 interconnected with a traffic light pole 360. Also shown is a COM device 100 interconnected with a traffic light 350. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate with a COM device 100 while the vehicle is stopped or passing through an intersection.

Referring to Figure 1G there is shown a COM device 100 interconnected with a change tollbooth 330. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate with a COM device 100 while the vehicle is in proximity of the change tollbooth 330 for the purpose of paying a toll.

Referring to Figure 1H there is shown a COM device 100 interconnected with a parking gate 316. Also shown is a COM device 100 interconnected with a parking terminal 352. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate with a COM device 100 while the vehicle is stopped or slowed at the parking gate 316, or the parking terminal 352

for the purpose of obtaining a ticket, calling, inserting a card, or obtaining some additional level of authorization or permission to pass through the gate. A parking gate 316, and parking terminal 352 can be similar to those used at many airports, parking garages, business parking lots, rental cars facilities, and other similar locations.

Referring to figure 1I there is shown a COM device 100 interconnected with a PC 310 located in a store 320. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate with a COM device 100 located in a store 320 from, for example and without limitation, the stores parking lot, collision repair center, service center, or other locations outside the store. The wireless data communication between COM device 100 and an in-vehicle device 200 can provide information about the vehicle including make, model, feature set, as well as diagnostic, vehicle telemetry, vehicle metrics, and other data.

In this regard, a potential application for the technology can be that an auto parts store could evaluate, diagnose, identify parts, or recommend vehicle service automatically. In addition, access to the Internet via PC 310, a COM device 100 or an in-vehicle device 200 can query information related to warranty, service, parts, coupons, special offers, and other vehicle service, or maintenance data. A store 320 can be any store, garage, collision repair center, service center, vehicle dealership, repair center, or other place of business. A store 320 can be a CAR QUEST, AUTOZONE, ADVANCE AUTO PARTS, CHIEF AUTO PARTS, DISCOUNT AUTO PARTS, PEP BOYS, NAPA, MOPAR AUTO PARTS, CSK AUTO (including CHECKER AUTO PARTS, SCHUCK'S AUTO SUPPLY, and KRAGEN AUTO PARTS), or other similar auto parts store.

09602971.062300

5 In an exemplary embodiment querying warranty information can include obtaining vehicle information from a database maintained and utilized in a retail store, or from a vehicle manufacturer database (i.e. GM, FORD, CHRYSLER, DIAMLER-BENZ, VOLKSWAGEN, TOYOTA, MAZDA, VOLVO, BMW, MERCEDES BENZ, PORSCHE, FERRARI, JAGUAR, NISSAN, SATURN, etc.), or other accessible databases. Querying part information can include obtaining part details, specifications, and availability from the retail store databases, Internet based databases, or Internet based auto parts and information companies such as WRENCHHEAD.COM, PARTS.COM, SPORTWING.COM, 10 CARPARTSONSALE.COM, CARPARTS.COM, NAPAONLINE.COM, PARTSAMERICA.COM, CSKAUTO.COM, ALLDATA.COM, MECHANICNET.COM, or other accessible databases.

15 Furthermore, while performing service on a vehicle or while running the vehicle in the parking lot, such as while the customer is parking their vehicle, data can be gathered about the vehicle. The wireless connection between a COM device 100, an in-vehicle device 200, the stores databases, or the Internet can allow for the recording of vehicle and engine performance data.

20 Use of this performance data can include tracking engine performance over time for different makes and models of vehicles, better serving customer needs, anticipating vehicle part requirements and service needs in an effort to sell customer's parts or services they may not know they need, or enhance warranty programs or offerings by the manufacture, parts suppliers, or stores to list a few.

25 Referring to Figure 1J there is shown a COM device 100 interconnected with a vehicle analyzer 328. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate vehicle and engine

performance to the vehicle analyzer 328, wherein such data can be analyzed, or data communicated to a database, or to an Internet based destination.

Referring to Figure 1K there is shown a personal data assistant (PDA) 324, and an Internet appliance 322. A PDA 324 can be a programmable storage device, such as a programmable storage device 368. A PDA 324 can be referred to as a pocket sized personal computer. A pocket sized personal computer can be a MICROSOFT POWER PC, a HEWLETT PACKARD JORNADO, or similar handheld pocket sized personal computer. An Internet appliance 322 can be a device, which has inherent in its design a primary application and multiple secondary applications. An Internet appliance 322 can be a COM device 100 or have a COM device 100 as part of an Internet appliance 322 embodiment.

For example and without limitation, a refrigerator can be equipped with an Internet appliance 322. In this embodiment an Internet appliance 322 can be a refrigerator control system and have a primary role of managing a refrigeration system. The Internet appliance 322 can also have a secondary role of connecting the refrigerator to the Internet, or providing wireless access to the Internet such that the Internet appliance 322 and refrigerator can data communicate with an Internet based server. Properly configured a refrigerator equipped with an Internet appliance 322 can serve as a wireless data link between devices such as COM device 100 or an in-vehicle device 200 and the Internet.

A second example of an Internet appliance 322 can be a wireless phone transceiver tower. In this example an Internet appliance 322 can be a wireless phone transceiver having a primary function of managing and conducting numerous simultaneous wireless voice and data phone communications. A secondary function of the wireless transceiver tower can be as a data conduit for

managing numerous wireless data communications for a plurality of COM device 100, or a plurality in-vehicle device 200 for the purpose of data communicating over the Internet to Internet based data processing resource.

5           In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate to either a PDA 324, or an Internet appliance 322. In operation this allows a PDA 324 device to display or effectuate changes to a vehicle equipped with an in-vehicle device 200 or effectuate changes to an in-vehicle device 200 by way of a wireless connection.

10           A PDA 324 and an in-vehicle device 200 can data communicate by way of direct wireless connection without reliance on an Internet appliance 322. Alternatively, a PDA 324, an in-vehicle device 200, and an Internet appliance 322 can data communicate with each other to allow seamless data communication  
15           between the devices or systems.

          In an exemplary embodiment an Internet appliance 322 can be a wireless telephone transceiver. In this embodiment an in-vehicle device 200 can maintain a wireless data communication in a similar fashion as a wireless or cellular  
20           telephone call. The PDA 324 can also establish and maintain a data connection to an Internet appliance 322. As such, data communication between an in-vehicle device 200 and a PDA 324 can be effectuated. In-vehicle device 200 and PDA 324 can data communicate through the same Internet appliance 322 or through different Internet appliances 322.

25           Furthermore, an in-vehicle device 200 can data communicate with an Internet appliance 322 for the purpose of obtaining Internet based, or other types of data or data resources. In addition, a PDA 324 can maintain a data connection

with an in-vehicle device 200 by way of an Internet appliance 322. In this regard all three devices or systems including an in-vehicle device 200, an Internet appliance 322, and a PDA 324 can freely data communicate between each device or system sharing data and accessing other data resources.

5

In another exemplary embodiment a PDA 322 can wirelessly connect to and data communicate with an in-vehicle device 200. A PDA 322 can be a MICROSOFT POCKET PC, HEWLETT PACKARD, CASIO, SHARP, PANASONIC, SANYO, SONY, 3COM PALM PILOT brand or type, or other similar brands or types of PDA. Wireless data communications can be by way of proprietary wireless standards and protocols, 3COM wireless standards and protocols, wireless application protocol (WAP), BLUE TOOTH compliant standards and protocols, small device microwave, spread spectrum, 900MHZ, or other suitable wireless standards, frequencies, or protocols.

10

15

Referring to Figure 1L there is shown a wireless phone 312, and an Internet appliance 322. A wireless phone 312 can be a programmable storage device, such as a programmable storage device 368. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate to either a wireless phone 312, or an Internet appliance 322. An Internet appliance 322 can be a COM device 100 or have a COM device 100 as part of an Internet appliance 322 embodiment.

20

25

In operation this allows a wireless phone 312 device to display or effectuate changes to a vehicle equipped with an in-vehicle device 200 or effectuate changes to an in-vehicle device 200 by way of a wireless connection.



A wireless phone 312 and an in-vehicle device 200 can data communicate by way of direct wireless connection without reliance on an Internet appliance 322. Alternatively, a wireless phone 312, an in-vehicle device 200, and an Internet appliance 322 can data communicate with each other to allow seamless data communication between the devices or systems.

In an exemplary embodiment an Internet appliance 322 can be a wireless telephone transceiver. In this embodiment an in-vehicle device 200 can maintain a wireless data communication in a similar fashion as a wireless or cellular telephone call. The wireless phone 312 can also establish and maintain a data connection to an Internet appliance 322. As such, data communication between an in-vehicle device 200 and a wireless phone 312 can be effectuated. In-vehicle device 200 and wireless phone 312 can data communicate through the same Internet appliance 322 or through different Internet appliances 322.

Furthermore, an in-vehicle device 200 can data communicate with an Internet appliance 322 for the purpose of obtaining Internet based, or other types of data or data resources. In addition, a wireless phone 312 can maintain a data connection with an in-vehicle device 200 by way of an Internet appliance 322. In this regard all three devices or systems including an in-vehicle device 200, an Internet appliance 322, and a wireless phone 312 can freely data communicate between each device or system sharing data and accessing other data resources.

In another exemplary embodiment a wireless phone 312 can wirelessly connect to and data communicate with an in-vehicle device 200. A wireless phone 312 can be an ERICSON, MOTOROLA, QUALCOM, AUDIOVOX, SPRINT, AT&T, OMNIPOINT, or other similar brands or types of wireless phones.

Referring to Figure 1M there is shown a pager 326, and an Internet appliance 322. A pager 326 can be a programmable storage device, such as a programmable storage device 368. In this embodiment an in-vehicle device 200 interconnected with a vehicle 314 can data communicate to either a pager 326, or an Internet appliance 322. An Internet appliance 322 can be a COM device 100 or have a COM device 100 as part of an Internet appliance 322 embodiment. In operation this allows a pager 326 to display or effectuate changes to a vehicle equipped with an in-vehicle device 200 or effectuate changes to an in-vehicle device 200 by way of a wireless connection.

A pager 326 and an in-vehicle device 200 can data communicate by way of direct wireless connection without reliance on an Internet appliance 322. Alternatively, a pager 326, an in-vehicle device 200, and an Internet appliance 322 can data communicate with each other to allow seamless data communication between the devices or systems.

In an exemplary embodiment an Internet appliance 322 can be a wireless telephone transceiver. In this embodiment an in-vehicle device 200 can maintain a wireless data communication in a similar fashion as a wireless or cellular telephone call. The pager 326 can also establish and maintain a data connection to an Internet appliance 322. As such, data communication between an in-vehicle device 200 and a pager 326 can be effectuated. In-vehicle device 200 and pager 326 can data communicate through the same Internet appliance 322 or through different Internet appliances 322.

Furthermore, an in-vehicle device 200 can data communicate with an Internet appliance 322 for the purpose of obtaining Internet based, or other types of data or data resources. In addition, a pager 326 can maintain a data connection

with an in-vehicle device 200 by way of an Internet appliance 322. In this regard all three devices or systems including an in-vehicle device 200, an Internet appliance 322, and a pager 326 can freely data communicate between each device or system sharing data and accessing other data resources.

5

In another exemplary embodiment a pager 326 can wirelessly connect to and data communicate with an in-vehicle device 200. A pager 326 can be a SKYTEL, MOTOROLA, QUALCOM, or other similar brands or types of pagers.

10

Referring to Figure 1N there is shown a programmable storage device 368. A programmable storage device 368 is a device capable of storing data transmitted wired or wirelessly from an in-vehicle device 200. Once data is stored within the programmable storage device 368 a user can physically carry the programmable storage device 368 to a alternative destination where the data within the programmable storage device 368 can be transferred to a COM device 15 100, or Internet appliance 322. Data can also be transferred from a COM device 100 or an Internet appliance 322 to the programmable storage device 368. A user can then carry the programmable storage to an in-vehicle device 200. Once at the in-vehicle device 200 the data within the programmable storage device 368 can be data communicated to the in-vehicle device 200. A programmable storage device 20 368 can be a vehicle key to start the engine.

25

In an exemplary embodiment a user can transfer data between an in-vehicle device 200, a COM device 100, an Internet appliance 322, and a programmable storage device 368. This can enable a user to transfer data from the vehicle interconnected with an in-vehicle device 200 to the programmable storage device 368 for the purpose of carrying the data to a location away from the vehicle. The user can then carry the programmable storage device 368 into, for

example and not limitation an auto part store. Once in the auto part store the data in the programmable storage device 368 can be data communicated to a COM device 100. The COM device 100 can then data communicate with additional data processing resources, such as a PC 310, or a global network based data processing resource.

A PDA 324, or a wireless phone 312, or a pager 326 can be a programmable storage device 368. In addition, a data key chain, or other portable storage device easily carried by a user can be utilized to implement a programmable storage device 368.

Referring to Figure 1P there is shown a plurality of store displays 370. Each store display 370 is equipped with a COM device 100. In an exemplary embodiment a store display 370 can include at least one COM device 100 as well as a plurality of products for sale (products for sale not shown). A customer can interact with the COM device 100 querying product information and accessing other types of digital content. A customer can utilize the COM device 100 to research product information, or identify the correct product or products and then make the physical selection from the store display 370, or request the assistance of a sales person to procure the product from warehouse stock, or other non-customer accessible stock area. In the event a product is not physically available or the customer desires to transact an e-commerce or e-business such a transaction can be performed by the customer at the COM device 100. A customer can interact with the COM device 100, such interaction can include transferring data between the COM device 100 and a wireless device, or a programmable device. In addition a customer can interact with a COM device 100 manually, including interaction through voice recognition, biometric recognition, a keypad, general purpose COM device 100 input or output, or touch screen input. In-vehicle device

200 data can be data communicated to the COM device 100 to aid in the digital content selection for the customer.

Referring to Figures 2A-2C there is shown a data communication network  
5 block diagram. Figure 2A shows data communication network connection  
between a plurality of data communicating devices and the Internet. The Internet  
can also be referred to as a global network.

Interconnected with proximity sensing parking light 354 is a COM device 100A. A COM device 100A can be a specific embodiment of a COM device 100. A COM device 100A can be interconnected with the Internet 362. A COM device 100A can also be interconnected with an Internet appliance 322A, which in turn the Internet appliance 322A can be interconnected with the Internet 362. COM device 100A can data communicate over the Internet by way of Internet appliance 322A. An Internet appliance 322A can be a specific embodiment of an Internet appliance 322.

Depending on the particular embodiment and user preferences the proximity sensing parking light 354 with COM device 100A combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select not to have a direct Internet connection.

25 In an embodiment where a COM device 100A selects not to have a direct Internet connection, a COM device 100A can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface,

wireless data link, LAN interface, or other wired or wireless communication means.

5 A COM device 100A can data communicate over the Internet by way of either the Internet appliance 322A data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of Internet service provider (ISP), a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a remote access server (RAS), by utilizing wireless Internet standards or protocols, or other Internet connection points or connection types.

10 The interconnections between a COM device 100A and the Internet appliance 322A, and between a COM device 100A and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100A can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

15 Interconnected with a parking proximity sensor 300 is a COM device 100B. A COM device 100B can be a specific embodiment of a COM device 100. A COM device 100B can be interconnected with the Internet 362. A COM device 100B can also be interconnected with an Internet appliance 322A, which in turn the Internet appliance 322A can be interconnected with the Internet 362. COM device 100B can data communicate over the Internet by way of Internet appliance 322A.

20 Depending on the particular embodiment and user preferences the parking proximity sensor 300 with COM device 100B combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of

methods to data communicate over the Internet, or select to not have a direct Internet connection.

5 In an embodiment where a COM device 100B selects not to have a direct Internet connection, a COM device 100B can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication  
10 means.

A COM device 100B can data communicate over the Internet by way of either the Internet appliance 322A data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by  
15 way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards or protocols, or other Internet connection points or connection types.

The interconnections between a COM device 100B and the Internet  
20 appliance 322A, and between a COM device 100B and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100B can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

25 Interconnected with a gas pump 304 is a COM device 100C. A COM device 100C can be a specific embodiment of a COM device 100. A COM device 100C can be interconnected with the Internet 362. A COM device 100C can also be interconnected with an Internet appliance 322A, which in turn the Internet

Depending on the particular embodiment and user preferences the gas pump 304 with COM device 100C combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

A COM device 100C can data communicate over the Internet by way of either the Internet appliance 322A data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

25           The interconnections between a COM device 100C and the Internet appliance 322A, and between a COM device 100C and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of



a COM device 100C can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

Interconnected with a garage door opener 302 is a COM device 100D. A  
5 COM device 100D can be a specific embodiment of a COM device 100. A COM  
device 100D can be interconnected with the Internet 362. A COM device 100D  
can also be interconnected with an Internet appliance 322A, which in turn the  
Internet appliance 322A can be interconnected with the Internet 362. COM device  
100D can data communicate over the Internet by way of Internet appliance 322A.

10 Depending on the particular embodiment and user preferences the garage  
door opener 302 with COM device 100D combination can selectively choose a  
single method to data communicate over the Internet 362, utilize a plurality of  
methods to data communicate over the Internet, or select to not have a direct  
15 Internet connection.

In an embodiment where a COM device 100D selects not to have a direct  
Internet connection, a COM device 100D can interface with a second data  
communicating device to gain access to the Internet. Data communication to a  
20 second device can be by way of a carrier current interface, a wireless transceiver,  
a network connection, modem or wireless modem, wireless phone interface,  
wireless data link, LAN interface, or other wired or wireless communication  
means.

25 A COM device 100D can data communicate over the Internet by way of  
either the Internet appliance 322A data connection or by way of a more direct  
connection to the Internet 362. A more direct connection to the Internet can be by  
way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a

RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

5           The interconnections between a COM device 100D and the Internet appliance 322A, and between a COM device 100D and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100D can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

10           A pager 326 can be interconnected with the Internet 362. Alternatively, a pager 326 can be interconnected with an Internet appliance 322B. The Internet appliance 322B can in turn be interconnected with the Internet 362. In both embodiments the pager 326 can data communicate over the Internet to a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet  
15           based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources. An Internet appliance 322B can be a specific embodiment of an Internet appliance 322.

20           Depending on the particular embodiment and user preferences the pager 326 can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select not to have a direct Internet connection.

25           In an embodiment where a pager 326 selects not to have a direct Internet connection, a pager 326 can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection,

modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

5 A pager 326 can data communicate over the Internet by way of either the Internet appliance 322B data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of an ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, or by utilizing wireless pager standards and protocols, or wireless Internet standards and protocols, or other Internet connection points or connection types.

10 The interconnections between a pager 326 and the Internet appliance 322B, and between a pager 326 and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a pager 326 can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

15 A PDA 324 can be interconnected with the Internet 362. Alternatively, a PDA 324 can be interconnected with an Internet appliance 322B. The Internet appliance 322B can in turn be interconnected with the Internet 362. In both 20 embodiments the pager 326 can data communicate over the Internet to a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources.

25 Depending on the particular embodiment and user preferences the PDA 324 can selectively choose a single method to data communicate over the Internet

5

10

15

20

25

Demographic Information	
Age	18-24
Gender	Male
Ethnicity	White
Education	High School
Occupation	Student
Income	\$10,000-\$15,000
Marital Status	Single
Religion	Christian
Political Affiliation	Democrat
Health Status	Good
Smoking Status	Non-smoker
Alcohol Consumption	Occasional
Exercise Frequency	Weekly
Stress Level	Low
Sleep Quality	Good
Dietary Habits	Vegetarian
Travel Frequency	Monthly
Family Size	2-3
Home Ownership	Renter
Vehicle Ownership	Yes
Internet Usage	Daily
Mobile Phone Usage	Daily
Social Media Usage	Daily
Volunteer Work	Yes
Charitable Contributions	Yes
Political Participation	Yes
Community Involvement	Yes
Life Satisfaction	High
Overall Well-being	Good

communicate over the Internet to a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources.

5                Depending on the particular embodiment and user preferences the wireless phone 312 can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select not to have a direct Internet connection.

10              In an embodiment where a wireless phone 312 selects not to have a direct Internet connection, a wireless phone 312 can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface,  
15              wireless data link, LAN interface, or other wired or wireless communication means.

                A wireless phone 312 can data communicate over the Internet by way of either the Internet appliance 322B data connection or by way of a more direct  
20              connection to the Internet 362. A more direct connection to the Internet can be by way of an ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, or by utilizing wireless phone standards and protocols, or a wireless Internet standards and protocols, or other Internet connection points or connection types.

25              The interconnections between a wireless phone 312 and the Internet appliance 322B, and between a wireless phone 312 and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of

a wireless phone 312 can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

A wireless phone 312 can be interconnected with the Internet 362.

5 Alternatively, a wireless phone 312 can be interconnected with an Internet appliance 322B. The Internet appliance 322B can in turn be interconnected with the Internet 362. In both embodiments the wireless phone 312 can data communicate over the Internet to a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources.

10 Depending on the particular embodiment and user preferences the wireless phone 312 can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select not to have a direct Internet connection.

15 In an embodiment where a wireless phone 312 selects not to have a direct Internet connection, a wireless phone 312 can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

20 A wireless phone 312 can data communicate over the Internet by way of either the Internet appliance 322B data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of an ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection,

25

a RAS connection, or by utilizing wireless phone standards and protocols, or wireless Internet standards and protocols, or other Internet connection points or connection types.

5           The interconnections between a wireless phone 312 and the Internet appliance 322B, and between a wireless phone 312 and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a wireless phone 312 can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

COM device 100E can also be interconnected with the Internet 362, and with an Internet appliance 322B. A COM device 100E can data communicate over the Internet by way of an Internet appliance 322B.

15 A COM device 100E and an in-vehicle device 200 can data communicate  
by way of a plurality of wired or wireless data communication means. A plurality  
of wired or wireless data communication means can include a carrier current  
interface, a wireless transceiver, a network connection, modem or wireless  
modem, wireless phone interface, wireless data link, LAN interface, or other  
20 wired or wireless communication means.

Depending on the particular embodiment and user preferences a COM device 100E can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

In an embodiment where a COM device 100E selects not to have a direct Internet connection, a COM device 100E can interface with a second data

communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

A COM device 100E can data communicate over the Internet by way of either the Internet appliance 322B data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing a wireless Internet standards and protocols, or other Internet connection points or connection types.

The interconnections between a COM device 100E and the Internet appliance 322B, and between a COM device 100E and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100E can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

An in-vehicle device 200 can data communicate over the Internet by way of an Internet appliance 322B. Depending on the particular embodiment and user preferences an in-vehicle device 200 can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

In an embodiment where an in-vehicle device 200 selects not to have a direct Internet connection, an in-vehicle device 200 can interface with a second data communicating device to gain access to the Internet. Data communication to



a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

5

An in-vehicle device 200 can data communicate over the Internet by way of either the Internet appliance 322B data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing a wireless Internet standards and protocols, or other Internet connection points or connection types.

10

15

The interconnections between an in-vehicle device 200 and the Internet appliance 322B, and between an in-vehicle device 200 and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100E can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

20

25

Referring to Figure 2B there is shown a data communication network connection between a plurality of data communicating devices and the Internet. Interconnected with a parking gate 316 is a COM device 100F. A COM device 100F can be a specific embodiment of a COM device 100. A COM device 100F can be interconnected with the Internet 362. A COM device 100F can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. COM device 100F can data communicate over the Internet by way of Internet appliance 322C. An Internet appliance 322C can be a specific embodiment of an Internet appliance 322.

00602971.06300

Depending on the particular embodiment and user preferences the parking gate 316 with a COM device 100F combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

In an embodiment where a COM device 100F selects not to have a direct Internet connection, a COM device 100F can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

A COM device 100F can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

The interconnections between a COM device 100F and the Internet appliance 322C, and between a COM device 100F and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100F can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

Interconnected with a parking terminal 352 is a COM device 100G. A COM device 100G can be a specific embodiment of a COM device 100. A COM device 100G can be interconnected with the Internet 362. A COM device 100G can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. COM device 100G can data communicate over the Internet by way of an Internet appliance 322C.

Depending on the particular embodiment and user preferences the parking terminal 352 with a COM device 100G combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

In an embodiment where a COM device 100G selects not to have a direct Internet connection, a COM device 100G can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

A COM device 100G can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

5 The interconnections between a COM device 100G and the Internet appliance 322C, and between a COM device 100G and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100G can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

10 Interconnected with a traffic light 350 is a COM device 100I. A COM device 100I can be a specific embodiment of a COM device 100. A COM device 100I can be interconnected with the Internet 362. A COM device 100I can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. COM device 100I can data communicate over the Internet by way of an Internet appliance 322C.

15 Depending on the particular embodiment and user preferences the traffic light 350 with COM device 100I combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

20 In an embodiment where a COM device 100I selects not to have a direct Internet connection, a COM device 100I can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, 25 a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

5 A COM device 100I can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

10 The interconnections between a COM device 100I and the Internet appliance 322C, and between a COM device 100I and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100I can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

15 A COM device 100H is mounted on a traffic light pole 360. A COM device 100H can be interconnected with a traffic light 350 or an emergency warning system (not shown). Furthermore, a COM device 100H can also be interconnected with the Internet 362 or interconnected with an Internet appliance 322C. In turn, the Internet appliance 322C can be interconnected with the Internet 362. A COM device 100H can data communicate over the Internet by way of an Internet appliance 322C. A COM device 100H can be a specific embodiment of a COM device 100.

25 In an exemplary embodiment a traffic light warning system can be optically responsive to oncoming emergency vehicles. An emergency warning system typically interfaces with the traffic light control system, such that when an emergency vehicle approaches the traffic light the warning system can by way of the traffic light control system activate the appropriate traffic lights to allow safe passage of the emergency vehicle through the intersection.

Interconnected with a wireless toll-pass system 308 is a COM device 100J. A COM device 100J can be a specific embodiment of a COM device 100. A COM device 100J can be interconnected with the Internet 362. A COM device  
5 100J can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. A COM device 100J can data communicate over the Internet by way of an Internet appliance 322C.

10 Depending on the particular embodiment and user preferences the wireless toll-pass system 308 with COM device 100J combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

15 In an embodiment where a COM device 100J selects not to have a direct Internet connection, a COM device 100J can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver,  
20 a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

25 A COM device 100J can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a

00602971.062300

RAS connection, by utilizing a wireless Internet standards and protocols, or other Internet connection points or connection types.

5           The interconnections between a COM device 100J and the Internet appliance 322C, and between a COM device 100J and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100J can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

10           Interconnected with a vehicle analyzer 328 is a COM device 100K. A COM device 100K can be a specific embodiment of a COM device 100. A COM device 100K can be interconnected with the Internet 362. A COM device 100K can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. COM device  
15           100K can data communicate over the Internet by way of Internet appliance 322C.

20           Depending on the particular embodiment and user preferences the vehicle analyzer 328 with COM device 100K combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

25           In an embodiment where a COM device 100K selects not to have a direct Internet connection, a COM device 100K can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface,

wireless data link, LAN interface, or other wired or wireless communication means.

5 A COM device 100K can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

10 The interconnections between a COM device 100K and the Internet appliance 322C, and between a COM device 100K and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100K can utilize one of the interconnections to the Internet, both  
15 of the interconnections to the Internet, or neither interconnection to the Internet.

Interconnected with a change tollbooth 330 is a COM device 100L. A COM device 100L can be a specific embodiment of a COM device 100. A COM device 100L can be interconnected with the Internet 362. A COM device 100L  
20 can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. A COM device 100L can data communicate over the Internet by way of Internet appliance 322C.

25 Depending on the particular embodiment and user preferences the change tollbooth 330 with COM device 100L combination can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods



to data communicate over the Internet, or select to not have a direct Internet connection.

5 In an embodiment where a COM device 100L selects not to have a direct Internet connection, a COM device 100L can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication  
10 means.

A COM device 100L can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by  
15 way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

The interconnections between a COM device 100L and the Internet  
20 appliance 322C, and between a COM device 100L and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100L can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or neither interconnection to the Internet.

25 Interconnected with a COM device 100M can be a PC 310A. Interconnected with a PC 310A can be a monitor 344, and a keyboard 348. A COM device 100M can be a specific embodiment of a COM device 100. A PC 310A can be a specific embodiment of a PC 310. A COM device 100M or a PC

310A can also be interconnected with an Internet appliance 322C, which in turn the Internet appliance 322C can be interconnected with the Internet 362. A COM device 100M or a PC 310A can data communicate over the Internet by way of an Internet appliance 322C.

5

In an exemplary embodiment a COM device 100M can be interconnected with a PC 310 and located in a store 320. A store 320 can be any store, garage, collision repair center, service center, vehicle dealership, repair center, or other place of business. A COM device 100M can then data communicate wirelessly with an in-vehicle device 200 (not shown). Such data communication can be telemetry information, vehicle metrics, or other data to facilitate vehicle service.

10

Depending on the particular embodiment and user preferences the COM device 100M or a PC 310A can selectively choose a single method to data communicate over the Internet 362, utilize a plurality of methods to data communicate over the Internet, or select to not have a direct Internet connection.

15

In an embodiment where a COM device 100M or a PC 310A selects not to have a direct Internet connection, a COM device 100M or a PC 310A can interface with a second data communicating device to gain access to the Internet. Data communication to a second device can be by way of a carrier current interface, a wireless transceiver, a network connection, modem or wireless modem, wireless phone interface, wireless data link, LAN interface, or other wired or wireless communication means.

20

25

A COM device 100L can data communicate over the Internet by way of either the Internet appliance 322C data connection or by way of a more direct connection to the Internet 362. A more direct connection to the Internet can be by

way of ISP, a TCP/IP connection, a PPP, SLIP, or SOCKET layer connection, a RAS connection, by utilizing wireless Internet standards and protocols, or other Internet connection points or connection types.

5           The interconnections between a COM device 100M or a PC 310A and the Internet appliance 322C, and between a COM device 100M or a PC 310A and the Internet 362 are mutually exclusive. In a plurality of exemplary embodiments, correct operation of a COM device 100M or a PC 310A can utilize one of the interconnections to the Internet, both of the interconnections to the Internet, or  
10           neither interconnection to the Internet.

Referring to Figure 2C there is shown a data communication network connection between a plurality of data communicating devices and the Internet. The Internet can also be referred to as a global network. In particular Figure 2C  
15           shows a plurality of exemplary embodiments of a system by which a plurality of COM device 100, a plurality of in-vehicle device 200, and a plurality of Internet based data processing resources can data communicate with one another.

A PC 310B can be interconnected with a COM device 100P or with the  
20           Internet 362. A COM device 100P can be a specific embodiment of a COM device 100. A PC 310B can be a specific embodiment of a PC 310. Furthermore, the COM device 100P can be interconnected with a COM device 100Q. A COM device 100Q can be a specific embodiment of a COM device 100.

25           In an exemplary embodiment a PC 310 can data communicate over the Internet 362. In addition, a COM device 100P can data communicate with a PC 310B and a plurality of COM device 100Q. In this embodiment a remote COM

device 100Q can forward, relay, or otherwise effectuate data communications with a COM device 100P.

5 Applications can include a collision repair center, service center with several garage work areas. In this application a plurality of COM device 100Q can data communicate with a COM device 100P data communicating vehicle telemetry, vehicle metrics, and other data to a COM device 100P or to a PC 310B for processing.

10 Interconnected with a PC 310C can be COM device 100R. A COM device 100R can be a specific embodiment of a COM device 100. A PC 310C can be a specific embodiment of a PC 310. A COM device 100R can be interconnected with a hub or concentrator 338A. A hub or concentrator 338A can be a specific embodiment of a hub or concentrator 338. Furthermore, a hub or concentrator  
15 338A can be interconnected with a router or gateway 340. A router or gateway 340 can be interconnected with the Internet 362. A hub or concentrator 338 can be CISCO, or other similar brands or types of hubs or concentrators. A router or gateway 340 can be CISCO, WHISTLE JET, or other similar brands or types of router or gateway.

20 In an exemplary embodiment a PC 310C and COM device 100R can data communicate by way of the hub or concentrator 338A and the router or gateway 340 over the Internet 362. Applications include a COM device 100R serving as a modem, data link, or other data connection device for a PC 310C, such that both a  
25 PC 310C and a COM device 100R can data communicate over the Internet.

Interconnected with a COM device 100N can be a hub or concentrator 338B. A hub or concentrator 338B can be a specific embodiment of a hub or

concentrator 338. A COM device 100N can be a specific embodiment of a COM device 100. A hub or concentrator 338B can be interconnected with a PC 310D. A PC 310D can be a specific embodiment of a PC 310. Furthermore, a PC 310D can be interconnected with the Internet 362.

5

In an exemplary embodiment a COM device 100N can data communicate with a PC 310D by way of the hub or concentrator 338B. Such data communication can be consistent with network protocol standards common to MICROSOFT NT, LINUX, UNIX, or NOVELL NETWARE applications and network architecture as well as other similar network applications and network architectures. In addition, a COM device 100N can data communicate over the Internet by way of the data connection to the PC 310D. Applications can include COM device 100N utilizing the PC 310D remote communication means to data communicate over the Internet 362. Remote communication means can include RAS, modem, LAN, and other wired and wireless remote communication means.

10

15

20

Interconnected with a COM device 100S can be the Internet 362. In an exemplary embodiment a COM device 100S can data communicate, access, or be accessed over the Internet by a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources.

25

Interconnected with an emergency monitoring network 332 can be the Internet 362. In an exemplary embodiment an emergency monitoring network 332 can data communicate to, access, or be accessed over the Internet by a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources. Access to the emergency monitoring network 332 can

include Internet, RAS, modem access, and other network access technologies. An emergency access network can be the national emergency agency 911 network, police networks, fire networks, medical networks, security networks, remote monitoring networks, surveillance networks, and other similar emergency access networks.

Applications can include a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources data communicating with an emergency monitoring network 332. Such data communication can be for the purpose of reporting, locating, or remotely disabling operation of a vehicle, notifying or requesting emergency service resultant from break in, theft, fire, or other emergency monitoring network data communications.

Interconnected with a virtual private network 334 can be the Internet 362. In an exemplary embodiment a virtual private network 334 can data communicate to, access, or be accessed over the Internet by a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources. Access to the virtual private network 334 can include Internet, RAS, modem access, and other network access technologies.

Interconnected with a personal PC network 336 can be the Internet 362. In an exemplary embodiment a personal PC network 336 can data communicate to, access, or be accessed over the Internet by a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing

resources. Access to the personal PC network 336 can include Internet, RAS, modem access, and other network access technologies.

5 Interconnected with an Internet appliance 322D is the Internet 362. An Internet appliance 322D can be a specific embodiment of an Internet appliance 322.

10 Interconnected with an Internet based server 364 can be the Internet 362 and a database 356A. A database 356A can be a specific embodiment of a database 356. In an exemplary embodiment a database 356A can be accessed by way of a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources. In addition, a database 356A can be accessible by way of an application, application server, a user, or a web browser. A web browser can be MICROSOFT'S INTERNET EXPLORER, NETSCAPE, NEUTRINO, PALM OS, WINDOWS CE, or other similar web browser technology. A database 356 can be based on MICROSOFT MS-ACCESS, SQL, DB2, ORACLE, or other similar database architectures. An Internet based server 364 can be a MICROSOFT NT, LINUX, APACHE, WHISTLE, NOVELL, UNIX, NEUTRINO, PALM OS, WINDOWS CE, WINDOWS 95-98, WINDOWS 2000 or other similar Internet capable server platform. Furthermore, an Internet based server 364 can be a mail server, database server, file transfer protocol (ftp) server, web server, transaction processing server, e-business server, e-commerce server, or other specialized server. An Internet based server 364 can be configured as an application server 358.

Interconnected with an Internet application server 358 can be the Internet 362 and a database 356B. A database 356B can be a specific embodiment of a

database 356. In an exemplary embodiment an Internet application server 358 or a database 356B can be accessed by way of a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based servers, a plurality of Internet appliances, or a plurality of other Internet based data processing resources. In addition, a database 356B can be accessible by way of an Internet application server 358, a local or remote application, a user, or a web browser.

In an exemplary embodiment an Internet application server 358 can be utilized to search for car parts in a database, or can process and maintain warranty information, or can process and store vehicle telemetry and vehicle metrics data. In addition, an Internet application server 358 can run a plurality of specific software applications and can data communicate with a plurality of COM device 100, or a plurality of in-vehicle device 200.

Referring to Figure 3 there is shown a communication interface device 100. A communication interface device 100 can be referred to as a COM device 100. A COM device 100 can be a device capable of data communicating wired or wirelessly with an in-vehicle device 200.

Interconnected with a microcontroller 130 can be a keypad 102. A keypad 102 can be an array of buttons. A keypad 102 utilizing an array of buttons can be implemented with a plurality of OMRON B3F-1100 push buttons, which can be organized in an array, or other functionally similar array of buttons. A microcontroller can be a ZILOG brand Z8, Z380C, or Z382 microcontroller, or a MOTOROLA brand HC series microcontroller. In addition, a microcontroller 130 can be an INTEL brand x86, CELERON, or PENTIUM microprocessor, or AMD brand microprocessor, or other similar microcontroller or microprocessor.



Interconnected with a microcontroller 130 can be an electrically erasable read only memory (EEROM/FLASH) 104. Such an EEROM 104 can be a MICROCHIP 27C512, an ATMEL FLASH AT27512, or other similar electrical read only memory. A one-time-programmable (OPT) read-only-memory (ROM) can be utilized to implement EEROM 104. FLASH memory can be used to implement an EEROM 104.

Interconnected with a microcontroller 130 can be a non-volatile memory/random access memory 106. Such a NOVRAM/RAM 106 can be a DALLAS SEMICONDUCTOR DS1643 or DS1743. Furthermore, the DS1643 or DS1743 can provide a non-volatile date and time function whereby microcontroller 130 can be responsive to or schedule events based on date and time, or date and time stamp transactions as they occur. Dynamic random access memory (DRAM) or static random access memory (SRAM), or other types of memory can be utilized to implement a NOVRAM/RAM 106.

In an exemplary embodiment a combination of non-volatile and volatile RAM, NOVRAM, DRAM, SRAM, and other types of memory can be utilized to implement a NOVRAM/RAM 106.

Further, NOVRAM/RAM 106 can be utilized to cache data communications between in-vehicle device 200 and the Internet. In addition, data can be cached from the wireless transceiver 134, and the plurality of communication interfaces. The plurality of communication interfaced can include the USB port 156, the PDA interface 120, the RS232/RS485 interface 116, the carrier current interface 132, the network connection to the Internet 136, the modem/wireless modem interface 138, the wireless phone transceiver 140, the

wireless phone interface 142, the wireless data link 144, or the local area network interface 146.

5 In addition, the NOVDRAM/RAM 106 can be utilized to store data, manage data flow between an in-vehicle device 200 and Internet data processing resources, convert data, and perform protocol conversions between data received through one interface and data communicated out through a second interface.

10 Interconnected with a microcontroller 130 can be an electrically erasable serial read only memory (serial EEROM/FLASH) 108. Such an EEROM 108 can be a MICROCHIP 93LC66, or ATMEL DATAFLASH serial EEROM.

15 Interconnected with a microcontroller 130 can be a magnetic card or smart card reader/writer 110. A magnetic card reader/writer 110 can be implemented with a NEURON brand MSR-100, or MSR-270, or a MAGNA TEC brand magnetic card or smart card reader/writer, or other similar track 1, 2 or 3 style magnetic card reader/writer or smart card reader/writer.

20 Interconnected with a microcontroller 130 can be a touch screen 112. A touch screen 112 can be implemented with a TRANSPARENT PRODUCTS, INC. part number TPI PN 1059-001, and a BURR BROWN touch screen controller part number ADS7843.

25 Interconnected with microcontroller 130 can be a liquid crystal display (LCD) 114. An LCD display 114 can be implemented by way of an OPTREX #DMF-5002NY-EB super-twist graphics module, or an OPTREX #DMC-6204NY-LY liquid crystal display, or an OPTREX #DMF-50944NCU-FW-1 and an EPSON SED1354FOA LCD controller.

Interconnected with a microcontroller 130 can be an RS232/RS485 interface 116. An RS232/RS485 interface 116 can be implemented by way of a MAXIM brand RS232 or RS485 transceiver series semiconductor. RS232 serial communications can be effectuated with a receive (RXD) data connection, transmit (TXD) data connection, clear to send data connection, ready to send (RTS) data connection, signal ground (GND) data connection. RS485 data communication can be effectuated with a pair of data connections (DATA "A" data connection and DATA "B" data connection).

Interconnected with a microcontroller 130 can be a general-purpose input and output interface 118. A general-purpose input and output interface 118 can be utilized to interface a COM device 100 to a plurality of external devices. Such external devices can include a garage door opener 302, a gas pump 304, a tollbooth 306, a wireless toll-pass system 308, a traffic light 350, a change tollbooth 330, a parking gate 316, a parking terminal 352, a vehicle analyzer 328, or a proximity sensing parking light 354.

In an exemplary embodiment a general-purpose input and output interface 118 can be tailored and effectuated in a plurality of ways based in part on the particular application. For example and without limitation, a general-purpose input and output interface 118 can be implemented with a plurality of relays, or a plurality of transistor-to-transistor-logic (TTL) inputs and outputs (I/O). A general-purpose input and output interface 118 can also be implemented with a plurality of opto-isolators, or a plurality of silicon controlled rectifiers (SCR), or a plurality of triacs, or a plurality of transistor drivers.

15

25

In an exemplary embodiment a COM device 100 can data communicate with a PDA by way of the PDA interface 120. In such an embodiment the PDA can exchange data and gain access to the Internet by way of the COM device 100. In addition, the PDA can receive data related to vehicle telemetry, metrics, and other informational data.

Interconnected with a microcontroller 130 can be a speech and sound audio playback means 124. In an exemplary embodiment a speech and sound audio playback means 124 can playback digitized and streamed audio data. In such an embodiment a data communication by way of the Internet can be played by the speech and sound audio playback means 124. In addition, pre-recorded audio data can be played by way of the speech and sound audio playback means 124. Such pre-recorded audio data can be ADPCM format, MP3 format, or other proprietary or standard data format. Furthermore, pre-recorded audio data can include instructional prompts and sounds, as well as warning prompts and other sounds. A speech and sound audio playback means 124 can be implemented with an OKI SEMICONDUCTOR MSM9841 or a OKI SEMICONDUCTOR MSM6585RS, or other similar speech or audio processors.

Interconnected with a speech and sound audio playback means 124 can be an amplifier and a filter network 126. An amplifier and a filter network 126 can be implemented with a SANYO LA4460N amplifier or TEXAS INSTRUMENTS amplifier. A filter network 126 can be implemented with a NATIONAL LM324 quad op-amp, or TEXAS INSTRUMENTS series DSP, or with a single pole resistor and capacitor combination. A speech and sound audio playback means 124 can also be implemented with other similar amplifiers and filter networks.

Interconnected with a speech and sound audio playback means 124 can be a speaker 128. A speaker 128 can be implemented with a variety of general-purpose speakers. Selection of a suitable speaker can be based in part on speaker size, shape, tonal qualities, as well as other design and application specification criteria.

Interconnected with a microcontroller 130 can be a carrier current interface 132. Carrier current interface 130 can be effectuated with traditional carrier current technologies, including spread spectrum technologies. Such a carrier current interface 132 can be implemented as desired and known by one skilled in the art of carrier current data communications.

In an exemplary embodiment a carrier current interface 132 can effectuate data communication with a PC 310. In this embodiment a COM device 100 by way of the carrier current interface 132 can data communication to a plurality of other COM device 100, or to a plurality of in-vehicle device 200, or to a plurality of Internet based servers, or to a plurality of Internet appliances, or to a plurality of other Internet based data processing resources.

Interconnected with a microcontroller 130 can be a wireless transceiver 134. In an exemplary embodiment a wireless transceiver 134 can be utilized to data communicate between a COM device 100 and an in-vehicle device 200. Such data communication can include vehicle telemetry, vehicle metrics, COM device 100 data, in-vehicle device 200 data, audio or video data, e-business data, e-mail data, e-commerce data, Internet based data, PC 310 data, as well as other general and specific data. A wireless transceiver 134 can be implemented with a BYTEL, DIGITAL WIRELESS CORPORATION, GLOBAL WAVE, FREEWAVE TECHNOLOGIES, ELECTRONIC SYSTEMS TECHNOLOGIES, GRE, IBM,

MOTOROLA, or other similar manufacturer of wireless transceiver products. A wireless transceiver 134 can also be implemented by terminating a wireless transceiver 134 interface as a PCMCIA interface. A PCMCIA compatible wireless device can then be electrically connected and utilized to effectuate wireless communications on any wireless technology, network, or system. A wireless transceiver 134 can be BLUE TOOTH compliant, wireless application protocol (WAP) compliant, or subscribe to other standard and proprietary wireless protocols or standards.

Interconnected with a microcontroller 130 can be a network connection to the Internet 136. In an exemplary embodiment a network connection to the Internet 136 can connect a COM device 100 to the Internet. A network connection to the Internet 136 can manage the TCP/IP stack if required and can implement a data security layer, SSL security socket, or other proxy, firewall, or encrypted security. In addition, the network connection to the Internet 136 can manage an encrypted packet protocol, or other network protocols.

In addition, a network connection to the Internet 136 can include a plurality of network and telecommunication interfaces including analog telephone line, T1, ADSL, DSL, ISDN, cable modem, satellite, or LAN interfaces including Ethernet, token ring, FIREWIRE, and other similar telecommunication and network interface technologies.

Interconnected with a microcontroller 130 can be a modem 138. A modem 138 can be a wireless modem. In an exemplary embodiment a modem 138 can be utilized to data communicate with a remote location. Such a remote location can be an emergency monitoring network 332, or a PC 310, or other remote location. A modem 138 can be implemented with a XECOM brand modem part number

5

10

15

25



data link 144 and can be implemented with an IBM, MOTOROLA, RESEARCH  
IN MOTION, MICROTEQ, or other similar RF transceiver technologies. A  
satellite receiver can be a wireless data link 144. Such a satellite receiver can be  
implemented with standards, protocols, service, communication equipment, or  
5 other technologies available from XM SATELLITE RADIO HOLDINGS, or  
SIRIUS SATELLITE RADIO, or other similar satellite technology companies.

Interconnected with a microcontroller 130 can be a local area network  
(LAN) interface 146. In an exemplary embodiment a LAN interface 146 can  
10 include Ethernet, token ring, FIREWIRE, and other standard networking  
interfaces. In addition, a LAN interface 146 can be utilized to effectuate data  
communication directly with a PC 310, or by way of a hub or concentrator 338 to  
a PC 310 or a router or gateway 340. A LAN 146 can effectuate COM device 100  
data communication over the Internet to a plurality of COM device 100, or to a  
15 plurality of in-vehicle device 200, or to a plurality of Internet based servers, or to  
a plurality of Internet appliances, or to a plurality of other Internet based data  
processing resources.

Interconnected with a microcontroller 130 can be a digital signal processor  
(DSP) 154. A DSP 154 can be a TEXAS INSTRUMENTS, or other similar DSP  
20 technology.

Interconnected with a video signal input and conditioner 150 can be a DSP  
154, or a video signal input and conditioner 150. A camera 148 can be  
25 interconnected with a video signal input and conditioner 150. Additionally, a DSP  
154 can be interconnected with a microphone 152.

In an exemplary embodiment a DSP 154 in combination with a camera 148, or a video signal input and conditioner 150, and a microphone 152 can be utilized to digitize audio and video signals. Once digitized these signals can be data communicated by way of a COM device 100. Data communication can include data communication over the Internet to a plurality of COM device 100, or to a plurality of in-vehicle device 200, or to a plurality of Internet based servers, to a plurality of Internet appliances, or to a plurality of other Internet based data processing resources. In addition, digitized audio can be utilized to effectuate voice activation of COM device 100.

Interconnected with a microcontroller 130 can be a universal serial bus interface 156. A universal serial bus interface can be referred to as a USB port 156, or USB interface 156. A USB port 156 is a standard data communication interface port.

Referring to Figure 4 there is shown an in-vehicle device 200. In-vehicle device 200 can be a device embodied in a vehicle. An in-vehicle device 200 can also be embodied in a vehicle battery, vehicle control system, vehicle alarm system, or an in-vehicle device 200 can be embodied in a separate enclosure and fastened to, or retrofitted to a vehicle. In an exemplary embodiment an in-vehicle device 200 can be located in a secure area within the vehicle. Such a secure area can include under the vehicle's hood, or in the vehicle's trunk.

Interconnected with a microcontroller 234 can be a keypad 202. A microcontroller 234 can be similar in manufacture, specification, or general electrical functionality to a microcontroller 130. A keypad 202 can be similar in manufacture, specification, or general electrical functionality to a keypad 102.

Interconnected with a microcontroller 234 can be an EEROM 204. An EEROM 204 can be similar in manufacture, specification, and general electrical functionality to an EEROM 104. Interconnected with a microcontroller 234 can be non-volatile memory/random access memory 206. A non-volatile memory/random access memory 206 can be similar in manufacture, specification, and general electrical functionality to a non-volatile memory/random access memory 106.

Interconnected with a microcontroller 234 can be a serial EEROM/FLASH 208. A serial EEROM 208 can be similar in manufacture, specification, and general electrical functionality to a serial EEROM/FLASH 108. In an exemplary embodiment a serial EEROM/FLASH 208 can be utilized as a high-density data storage area. Such a high-density data storage area can be utilized for storage of digital audio data, video data, text data, display data, telemetry data, metric data, or other types of data.

Interconnected with a microcontroller 234 can be non-volatile memory/random access memory 206. A non-volatile memory/random access memory 206 can be similar in manufacture, specification, and general electrical functionality to a non-volatile memory/random access memory 106.

Interconnected with a microcontroller 234 can be a vehicle engine control system interface 210. The vehicle engine control system interface 210 can include interconnections to a vehicle communication bus. Such a vehicle communication bus can carry data communication to a plurality of systems and devices within the vehicle. Vehicle bus protocols and standard can include proprietary protocols and standards, or conform and support standard vehicle bus protocols and standards. Standard vehicle bus protocols and standards can include CONTROL AREA

NETWORK (CAN), LOCAL INTERCONNECT NETWORK (LIN), J1850, INTELLIGENT TRANSPORTATION SYSTEM DATA BUS (IDB), and IDB-MULTIMEDIA protocols and standards.

5           In an exemplary embodiment a vehicle engine control system interface 210 can interface and data communicate with a vehicle engine control system such that engine telemetry, metrics, efficiency, settings, or other vehicle and engine data can be data communicated for processing. Data communication for processing can include data communicating over the Internet, or to a plurality of  
10       COM device 100, or to a plurality of in-vehicle device 200, or to a plurality of Internet based servers, or to a plurality of Internet appliances, or to a plurality of other Internet based data processing resources.

15           In such an embodiment data communication between a vehicle engine control system interface 210 and a vehicle engine control system can effectuate remote diagnostics, repairs, adjustment to the engine control system, as well as other vehicle maintenance, monitoring, or adjustments. Such data communication can be between a remote location, over the Internet, between a plurality of COM device 100, between a plurality of in-vehicle device 200, between a plurality of  
20       Internet based servers, between a plurality of Internet appliances, or between a plurality of other Internet based data processing resources.

25           Interconnected with a microcontroller 234 can be a magnetic card or smart card reader/writer 212. A magnetic card or smart card reader/writer 212 can be similar in manufacture, specification, and general electrical functionality to a magnetic card or smart card reader/writer 110.

Interconnected with a microcontroller 234 can be a touch screen 214. As part of a user interface the touch screen 214 can be electrically tethered separate from the in-vehicle device 200. A touch screen 214 can be similar in manufacture, specification, and general electrical functionality to a touch screen 114.

5 Interconnected with a microcontroller 234 can be an LCD display 216. A LCD display 216 can be similar in manufacture, specification, and general electrical functionality to a LCD display 114.

10 Interconnected with a microcontroller 234 can be an RS232/RS485 interface 218. An RS232/RS485 interface 218 can be similar in manufacture, specification, and general electrical functionality to an RS232/RS485 interface 116. In an exemplary embodiment an RS232/RS485 interface 218 can be utilized to effectuated data communication with an RS232/RS484 compliant device, including a notebook computer. A notebook computer can be a DELL, SONY,  
15 GATEWAY, IBM, IBM brand THINKPAD, or other similar type of notebook computer. Such data communication can be between a remote location, over the Internet, between a plurality of COM device 100, between a plurality of in-vehicle device 200, between a plurality of Internet based servers, between a plurality of Internet appliances, or between a plurality of other Internet based data processing  
20 resources.

Interconnected with microcontroller 234 can be a general-purpose input and output interface 220. A general-purpose input and output interface 220 can be utilized to interface an in-vehicle device 200 to a plurality of in vehicle devices.  
25 Such in vehicle devices can include engine components, gauges, relays, ignition controls, cruise control, air conditioner controls, and other vehicle controls. A general-purpose input and output interface 220 can include support for CAN

network interfacing, LIN network interfacing, J1850, IDB network interface, or IDB-MULTIMEDIA network interface.

5 In an exemplary embodiment a general-purpose input and output interface 220 can be tailored and effectuated in a plurality of ways based in part on the particular application. For example and without limitation, a general-purpose input and output interface 220 can be implemented with a plurality of relays, or a plurality of transistor-to-transistor-logic (TTL) inputs and outputs (I/O). A general-purpose input and output interface 118 can also be implemented with a  
10 plurality of opto-isolators, or a plurality of silicon controlled rectifiers (SCR), or a plurality of triacs, or a plurality of transistor drivers.

A general-purpose input and output interface 220 can be similar in manufacture, specification, or general electrical functionality to a general-purpose  
15 input and output interface 118.

Interconnected with a microcontroller 234 can be a personal data assistant (PDA) interface 222. A PDA interface 222 can be implemented with an infrared communications means or a wired interface. An infrared communications means  
20 can be implemented with an infrared remote control receiver module, such as a LITEON LT1033, and an infrared LED for transmitting data, such as a LITEON LT1062 LED. A PDA interface 222 can also be a wired interface. A wired interface can be implemented with the 3COM PALM PILOT interface cable, or other PDA brand interface cables. In addition, a wireless PDA interface 120 can  
25 be implemented utilizing wireless standards such as wireless application protocol (WAP), BLUE TOOTH, or other wireless standards and protocols.

5 In an exemplary embodiment an in-vehicle device 200 can data communicate with a PDA by way of the PDA interface 222. In such an embodiment the PDA can exchange data and gain access to the Internet by way of an in-vehicle device 200. In addition, the PDA can receive data related to vehicle telemetry, metrics, and other informational data.

10 Interconnected with a microcontroller 234 can be a speech and sound audio playback means 224. In an exemplary embodiment a speech and sound audio playback means 224 can play back digitized, and streamed audio data. In such an embodiment a data communication by way of the Internet can be played by the speech and sound audio playback means 224. In addition, pre-recorded audio data can be play by the speech and sound audio playback means 224. Such pre-recorded audio data can be ADPCM format, MP3 format, or other proprietary or standard data format. In addition, pre-recorded audio data can include  
15 instructional prompts and sounds, as well as warning prompts and sounds, and other audible prompts and sounds. A speech and sound audio playback means 224 can be implemented with an OKI SEMICONDUCTOR MSM9841 or a OKI SEMICONDUCTOR MSM6585RS, or other similar speech and audio processors.

20 Interconnected with the speech and sound audio playback means 224 can be an audio switch 226. The audio switch 226 can be interconnected with the microcontroller 234. In an exemplary embodiment the audio switch 226 being responsive to the microcontroller 234 can route audio signals to an in-vehicle device 200 audio amplifier 228, or to the vehicle radio interface 248. In this  
25 embodiment the audio switch 226 allows analog and digital signals from an in-vehicle device 200 to be data communicated to the vehicle's radio by way of the vehicle interface 248. This allows the vehicle radio to serve as the audio system for playback, and audio conferencing. A vehicle radio interface 248 can be





An alarm system interface 236 can be implemented with line level analog inputs, through TTL level or digital line driven inputs and outputs, or through small signal relays. A proximity sensor 238 can be implemented with an ALLEN BRADLEY, GENERAL ELECTRIC, OMRON, NATIONAL, or other similar proximity sensor. A motion sensor 240 can be implemented with an ANALOG DEVICE, ANALOG DEVICE iMEMS technology, or other similar motion sensor. A current loop sensor 242 can be implemented with a toroid coil, or other similar current loop sensor. An ignition kill interface 238 can be implemented with an OMRON relay, or other similar relay.

Interconnected with a microcontroller 234 can be a digital signal processor (DSP) 232. A DSP 232 can be a TEXAS INSTRUMENTS, or other similar DSP technology.

Interconnected with a video signal input and conditioner 252 can be a DSP 232, or a video signal input and conditioner 252. A camera 250 can be interconnected with a video signal input and conditioner 252. Additionally, a DSP 232 can be interconnected with a microphone 254.

A user interface can include a combination of in-vehicle device 200 features. Such combination of in-vehicle device 200 features can include the touch screen 214, the LCD display 216, and the microphone 254. Other user interface devices can be included in the user interface as required by the specific application. In certain embodiments it may be required, or desirable to locate the user interface in the vehicle's passenger compartment area and electrically tether the user interface to the in-vehicle device 200 which may reside in the vehicle trunk, engine area, or elsewhere in the vehicle. This in effect allows the in-vehicle device to reside in a secure area of the vehicle while the user interface

components remain accessible by a user from within the vehicle's passenger compartment area.

5 In an exemplary embodiment a DSP 232 in combination with a camera 250, or a video signal input and conditioner 252, or a microphone 254 can be utilized to digitize audio and video signals. Once digitized these signals can be data communicated by way of an in-vehicle device 200. Data communication can include data communication over the Internet to a plurality of COM device 100, to a plurality of in-vehicle device 200, to a plurality of Internet based servers, to a plurality of Internet appliances, or to a plurality of other Internet based data processing resources. In addition, digitized audio can be utilized to effectuate voice activation of in-vehicle device 200. Such voice activation can invoke command and control features such as vehicle command and control, in-vehicle device 200 command and control, or other command and control functions and features. Such vehicle command and control can include operation and control of the vehicle and vehicle system including the engine, braking, gas pedal, ignition, and stick shift.

20 Interconnected with a microcontroller 234 can be an ignition control interface 256. An ignition control interface 256 allows the in-vehicle device 200 to start a car that is turned 'OFF' or stop a car that is turned 'ON'. An ignition control interface can be implemented with an OMRON relay, or other similar relay. An ignition control interface 256 can include support for CAN network interfacing, LIN network interfacing, J1850, IDB network interface, or IDB-MULTIMEDIA network interface.

25 Interconnected with a microcontroller 234 can be a wireless transceiver 258. In an exemplary embodiment a wireless transceiver 258 can be utilized to

data communicate between a COM device 100 and an in-vehicle device 200. Such data communication can include vehicle telemetry, vehicle metrics, COM device 100 data, in-vehicle device 200 data, audio or video data, e-business data, e-mail data, e-commerce data, Internet based data, PC 310 data, as well as other general and specific data. A wireless transceiver can be implemented with a BYTEL, DIGITAL WIRELESS CORPORATION, GLOBAL WAVE, FREEWAVE TECHNOLOGIES, ELECTRONIC SYSTEMS TECHNOLOGIES, GRE, IBM, MOTOROLA, or other similar manufacturer of wireless transceiver products. A wireless transceiver 258 can also be implemented by terminating a wireless transceiver 258 interface as a PCMCIA interface. A PCMCIA compatible wireless device can then be electrically connected and utilized to effectuate wireless communications on any wireless technology, network, or system. A wireless transceiver 258 can be BLUE TOOTH compliant, wireless application protocol (WAP) compliant, or subscribe to other standard and proprietary wireless protocols or standards.

Interconnected with a microcontroller 234 can be a vehicle monitor and metering interface 260. A vehicle monitor and metering interface 260 can include support for CAN network interfacing, LIN network interfacing, J1850, IDB network interface, or IDB-MULTIMEDIA network interface.

In addition, a vehicle monitor and metering interface 260 can include certain vehicle monitor and metering means. Certain vehicle monitor and metering means can include an accelerometer 262, a tachometer RPM/speed 264, and an odometer 266. By interconnecting a vehicle monitor and metering interface 260 with vehicle gauges and instrumentation the in-vehicle device 200 can monitor, record, and data communicate vehicle telemetry and metrics. In an embodiment where an interface to certain instrumentation may not be possible or

Interconnected with a microcontroller 234 can be a global satellite positioning (GPS) receiver 268. A GPS receiver 268 can receive signals from satellites and determine the locations of the GPS receiver and the vehicle containing the GPS receiver. This GPS location data can be data communicated to the in-vehicle device 200 and further processed as required. A GPS receiver 268

can be implemented with a GARMIN, MAGELLAN, LOWRANCE, or other similar GPS receiver models or brands.

Interconnected with a microcontroller 234 can be a wireless modem 270.

5 In an exemplary embodiment a wireless modem 270 can be utilized to data communicate with a remote location. Such a remote location can be an emergency monitoring network 332, or a PC 310, or other remote location. A wireless modem 270 can be implemented with an IBM, MOTOROLA, TELETRONICS, TELEDISIGN SYSTEMS, or other similar types of wireless modem. A wireless  
10 modem 270 can also be a PCMCIA interface connector. In this embodiment a PCMCIA interface connector can allow a wide variety of off-the-shelf brands of wireless modem to interconnect and operate with an in-vehicle device 200.

Interconnected with a microcontroller 234 can be a wireless or cellular  
15 phone transceiver 272. In an exemplary embodiment a wireless or cellular phone transceiver 272 can be utilized to effectuate data communication between an in-vehicle device 200 and a wireless or cellular network. A wireless or cellular phone transceiver 272 can be implemented with an IBM, GLOBAL WAVE, NOVATEL WIRELESS, MOTOROLA, or other similar wireless or cellular  
20 phone transceiver.

Interconnected with a microcontroller 234 can be a wireless or cellular  
phone interface 274. In an exemplary embodiment a wireless or cellular phone interface 274 can be utilized to interface a wireless or cellular phone to an in-  
25 vehicle device 200. In this embodiment a wireless or cellular phone interface 274 can enable an in-vehicle device 200 to utilize wireless or cellular phone functionality including, processing voice and data signals, or data communicate by way of a wireless or cellular network.

Interconnected with a microcontroller 234 can be a wireless data link 276. An infrared communications means can be a wireless data link 276, and can be implemented with an infrared remote control receiver module, such as a LITEON  
5 LT1033, and an infrared LED for transmitting data, such as a LITEON LT1062 LED. A radio frequency (RF) transceiver can be a wireless data link 276 and can be implemented with an IBM, MOTOROLA, RESEARCH IN MOTION, MICROTEQ, or other similar RF transceiver technologies. Such a satellite receiver can be implemented with standards, protocols, service, communication  
10 equipment, or other technologies available from XM SATELLITE RADIO HOLDINGS, or SIRIUS SATELLITE RADIO, or other similar satellite technology companies.

Interconnected with a microcontroller 234 can be a printer interface 278. A printer interface can interface to serial printers as well as parallel or CENTRONIC or USB style printers. In an exemplary embodiment a printer interface 278 can interface to a printer for the purpose of printing Internet based data, vehicle telemetry or metric data, advertising data, or other print data. A  
20 printer interface 278 can be implemented with a TTL level line input and output driver or a TTL or RS232 level serial interface. A TTL level interface can be an ALEGRO UCN5801EP or UDN2595A, or a CYPRESS CPLD 371 series. A serial printer interface can be implemented with a MAXIM RS232 converter/interface, or TTL level ALEGRO UDN2595A, or a CYPRESS CPLD  
25 371 series, or other similar devices.

Interconnected with a microcontroller 234 can be a biometric input interface 280. A biometric input interface 280 can accept and or process palm,

hand, finger, eye (iris scan), voice and voice commands, or other biometric input data. A biometric input interface can be a TTL, or RS232, or third party proprietary interface. In addition, a biometric input interface 280 can interface to a third party biometric devices. A biometric input interface 280 can be implemented with a TTL level line interface such as an ALEGRO UCN5801EP, or UDN2595A, or a CYPRESS CPLD 371 series, or other similar circuit interfaces. A serial biometric input interface can be implemented with a MAXIM RS232 converter/interface, or TTL level ALEGRO UDN2595A, or a HARRIS SEMICONDUCTOR, CYPRESS SEMICONDUCTOR, or other similar circuit interfaces.

Interconnected with a microcontroller 234 can be a universal serial bus interface 282. A universal serial bus interface can be referred to as a USB port 282, or USB interface 282. A USB port 282 is a standard data communication interface port.

Referring to Figure 5 there is shown a radio interactive digital content and advertisement content server routine 400. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the radio interactive digital content and advertising content routine 400. The radio interactive digital content and advertisement server can be an Internet based server that receives data communication from a COM device 100 or an in-vehicle device 200. Then based in part on known user preferences or profile and based in part on GPS data or geographic location data the Internet based interactive digital content and advertisement content server can select content from a database of content and serve the content to a specific COM device 100, or a specific in-vehicle device 200. Alternatively, the interactive digital content and

advertisement server can serve content to a plurality of COM device 100, or a plurality of in-vehicle device 200. Processing begins in block 402.

5 Processing in block 402 allows a user to initiate the usage of the vehicle radio. In an exemplary embodiment an in-vehicle device 200 can monitor the usage of the radio including the radios settings. Radio settings can include radio frequency (radio station) listening preferences, duration of listening, time of the day and days of the week listening, and measure a users tendency to change the radio station when commercials are broadcast. Processing then moves to block 10 404.

15 In block 404 data communication between an in-vehicle device 200 and a COM device 100, a second in-vehicle device 200, an Internet based server, or an Internet appliances can be established. Such a data communication can allow data to be exchanged between an Internet based server and an in-vehicle device 200. Such data communication can include user preferences, and other user metrics, or listening histories including radio frequency (radio station) listening preferences, duration of listening, time of the day and days of the week listening, and measure a user's tendency to change the radio station when commercials are broadcast. In 20 addition, data communication between the in-vehicle device 200 and an Internet based server allows both the server and the in-vehicle device 200 to be programmed, or update other elements within a plurality of databases. Processing then moves to block 406.

25 In block 406 GPS data can be data communicated between the Internet based server and the in-vehicle device 200. Such GPS data communication can be utilized in the selection of interactive digital content and advertisement content based in part on geographic location. In addition, any command and control



functionality such as stopping the engine, monitoring engine performance, trip tracking, or reporting car positioning can be data communicated. Processing then moves to block 408.

5 In block 408 an Internet based server selects interactive digital content and advertisement content based on certain interactive digital content and advertisement content selection criteria. Such content selection criteria can include selection based in part on GPS positioning data. Content selection based on GPS data in essence is content selection based on the geographic location of the vehicle. In this embodiment, interactive digital content and advertisement content selection criteria, based on GPS data can result in content for local restaurants, shopping, site seeing attractions, etc. can be served and displayed in a vehicle moving down a highway.

Interactive digital content and advertisement content selection can also be based on radio station selection and user's listening histories. User listening histories can include radio frequency (radio station and types of songs including specific song titles) listening preferences, duration of listening, time of the day and days of the week listening, and measure a user's tendency to change the radio station when commercials are broadcast. Such listening history data can be monitored or recorded by way of a vehicle radio interface 248.

In addition, content selection can be based on cookies resident on an Internet server, or in a user's in-vehicle device 200. In addition to cookies other user specific data can be maintained at the server or within the user's in-vehicle device 200. Such other users specific data can include a user's buying habits, listening habits, and other user demographics.

In other embodiments interactive digital content and advertisement content can be selected based on database queries, and other content serving based criteria and processes. Processing then moves to block 410.

5 In block 410 interactive digital content or advertisement content are data communicated between the Internet based server and a specific COM device 100, or a specific in-vehicle device 200. Processing then moves to block 412.

10 Processing in block 412 allows a user to interact with the digital content or advertisement content. Interaction with the content can include sending or receiving an e-mail, or conducting an e-commerce or e-business type transaction. Processing then moves to block 414.

15 In block 414 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

20 Referring to Figure 6 there is shown an Internet based remote control vehicle alarm routine 500. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the vehicle alarm routine 500. In an exemplary embodiment an Internet based remote control  
25 vehicle alarm can be utilized to notify an Internet based data processing resource, server, or agency that a vehicle alarm has been activated. In addition, the Internet based data processing resource, server, or agency can initiate a command and control level of functionality such that, a equipped with an vehicle in-vehicle

device 200 can receive a data communication and act upon such data including deactivating the vehicle's engine. Processing begins in block 502.

5 In block 502 the police, law enforcement, national emergency agency 911, a user, central monitoring station, or other agency desiring to located or stop a specific vehicle equipped with an in-vehicle device 200 can be identified. Processing then moves to block 504.

10 In block 504 the police, law enforcement, national emergency agency 911, a user, central monitoring station, or other agency desiring to located or stop a specific vehicle can via Internet access set a flag or otherwise program a server with appropriate instructions. Appropriate instructions, can include setting a flag, or programming a server, requesting the vehicle to report its GPS position, or instructing the in-vehicle device 200 associated with a particular vehicle to stop  
15 the vehicle. Stopping the vehicle can be done by way of the interface to the vehicle engine control system 210, or the ignition control interface 256. Processing then moves to block 506.

20 In block 506 flagged conditions and GPS data requests can be data communicated between a specific in-vehicle device 200, a COM device 100, an Internet based server, or an Internet appliance. Processing then moves to block 508.

25 In block 508 the vehicle associated with the specific in-vehicle device 200 receives the flagged condition, or GPS data request and executes the command and control functionality. Such command and control functionality can include stopping the engine, or reporting vehicle GPS positioning. Processing then moves to block 510.

In block 510 a confirmation of executed command and control functions including success and failure confirmation can be data communicated between a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Such data communication can serve as notification to the police, law enforcement, national emergency agency 911, a user, central monitoring station, or other agency that the vehicle has been or has not been located, or stopped. Such data can include the vehicle's GPS location. Processing then moves to block 512.

In block 512 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

Referring to Figure 7 there is shown an Internet based voice and data communication routine 600. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate voice and data communication routine 600. An Internet based voice and data communication routine effectuates audio and videoconferencing from within a vehicle by way of an in-vehicle device 200, a COM device 100, a second in-vehicle device 200, an Internet based server, or an Internet appliance. Processing begins in decision block 604.

In decision block 604 a user is allowed to select whether to open a microphone or video feed. If the resultant is in the affirmative, that is the user

decides to open a microphone or video feed then processing moves to block 602. In the resultant is in the negative, that is the user does not decide to open a microphone or video feed then processing moves to decision block 606.

5           In an exemplary embodiment audio conferencing can be effectuated by way of microphone 254. In addition, videoconferencing can be effectuated by way of camera 250, and video signal input and conditioner 252. In this embodiment audio or video signals can be digitized by way of DSP 232 and data communicated between an in-vehicle device 200 and other COM device 100,  
10           other in-vehicle device 200, or other Internet resources. Audio or Video signals can be data communicated to an in-vehicle device 200 and broadcast or shown by way of the LCD display 216, and the speech and sound audio playback means 224. Audio playback can be by way of an in-vehicle device 200 sound system including amplifier and filter network 228, and speaker 230. Alternatively,  
15           playback can be through the vehicle's radio by way of vehicle radio interface 248. In this embodiment an audio switch 226 can select between playback systems (in-vehicle device 200 or vehicle radio).

20           In block 602 the in-vehicle device 200 associated with the user's vehicle opens a microphone or a video feed. In addition, data communication between a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance is effectuated. Processing then moves to decision block 608.

25           In decision block 608 the user is allowed to close the microphone or video feed. If the resultant is in the affirmative, that is the user desires to close the microphone or video feed then processing moves to block 610. If the resultant is in the negative, that is the user does not desire to close the microphone or video feed then processing moves to decision block 606.

In block 610 the microphone or video feed is closed and processing then moves to block 614.

5           In block 614 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

10           In decision block 606 a determination is made based on data communication received by the in-vehicle device 200. If the resultant is in the affirmative, that is data communications are received requesting the in-vehicle device 200 to open a microphone or video feed then processing moves to block 612. If the resultant is in the negative, that is the in-vehicle device 200 does not receive data communications requesting the in-vehicle device 200 to open a microphone or video feed then processing moves to block 614.

15           In block 612 the in-vehicle device 200 opens the microphone or video feed based on data communication requests from a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Processing then moves to decision block 616.

20           In decision block 616 a determination is made based on data received by the in-vehicle device 200. If the resultant is in the affirmative, that is in-vehicle device 200 receives a data communication requesting the closing of the microphone or video feed then processing moves to block 610. If the resultant is

in the negative, that is in-vehicle device 200 does not receive a data communication requesting the closing of the microphone or video feed then processing moves to decision block 618.

5           In decision block 618 a determination is made based on user input. If the resultant is in the affirmative, that is a user selects to close a microphone or video feed then processing moves to block 610. If the resultant is in the negative, that is the user does not select to close the microphone or video feed then processing moves to block 616.

10           Referring to Figure 8A-8B there is shown an Internet based vehicle alarm routine 700. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate Internet based vehicle alarm routine 700. An Internet based vehicle alarm system effectuates setting and  
15           monitoring of a vehicle's security system by way of the Internet. In such an embodiment a user can set the alarm and allow a central station to monitor the vehicle status, including the alarm state by way of an Internet connection or an Internet based server. Processing begins in decision block 702.

20           In decision block 702 a determination is made based on user input or based on data communication between the in-vehicle device 200 and a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. If the resultant is in the affirmative, that is user input or data communication from a COM device 100, a specific in-vehicle device 200, an  
25           Internet based server, or an Internet appliance desires to turn the alarm system 'ON' then processing moves to block 704. If the resultant is in the negative, that is user input or data communication from a COM device 100, a specific in-vehicle

device 200, an Internet based server, or an Internet appliance does not desire to turn the alarm system 'ON' then processing moves to decision block 708.

5 In block 704 the vehicle alarm system is turned 'ON'. In an exemplary embodiment a vehicle's alarm system can be activated by way of the alarm system interface 236. In such an embodiment the alarm system interface 236 can include certain alarm circuitry. Certain alarm circuitry can include a proximity sensor 238, a motion sensor 240, a current loop sensor 242, or an ignition kill interface 246. In vehicles equipped with an in-vehicle device 200 and a separate alarm system the alarm system interface 236 can interface to and data communicate with the separate alarm system by way of the alarm system interface 236.

10 Alternatively, in embodiments where interfacing to a separate alarm system may not be possible an in-vehicle device 200 and a microphone 254 can be utilized to monitor the vehicle noise level and activate an alarm condition based in part on alarm siren noise, or other detected noise. Processing then moves to block 710.

20 In decision block 708 a determination is made based on user input or based on data communication between the in-vehicle device 200 and a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. If the resultant is in the affirmative, that is user input or data communication from a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance desires to turn the alarm system  
25 'OFF' then processing moves to block 706. If the resultant is in the negative, that is user input or data communication from a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance does not desire to turn the alarm system 'OFF' then processing moves to decision block 712.



Processing in block 706 deactivates the alarm system. Processing then moves to block 710.

5 In block 710 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

10 In decision block 712 a determination can be made based on the status of the alarm. If the resultant is in the affirmative, that is an alarm condition is detected (the alarm has been triggered) then processing moves to block 714. If the resultant is in the negative, that is the alarm condition is not detected (the alarm has not been triggered) then the routine is exited.

15 In block 714 the status of the alarm condition (triggered, or not triggered) and the vehicle GPS location data are data communicated between a COM device 100, an in-vehicle device 200, an Internet based server, or an Internet appliance. Processing then moves to block 716.

20 In block 716 a COM device 100, a specific in-vehicle device 200, an Internet based server, or an Internet appliance can set a flag to have the vehicle continuously report vehicle GPS location data, stop the vehicle engine, reset the alarm, or take other appropriate action. Appropriate action determination can be based in part on user preferences, server programming, central station monitoring procedures, police or law enforcement or national emergency agency 911



from the server can be directed to and processed by the police networks, law enforcement networks, national emergency agency 911 networks, or other agency networks. Processing begins in block 724.

5           In block 724 a COM device 100, an in-vehicle device 200, an Internet based sever, or an Internet appliance having detected an alarm condition data communicates with an Internet based server. Processing then moves to block 726.

10           In block 726 based on user preferences, server programming, or central station monitoring procedures a response from the server can be issued. In addition, responses from the server can be directed to and processed by the police networks, law enforcement networks, national emergency agency 911 networks, other agency networks. The routine is then exited.

15           Referring to Figure 9 there is shown an Internet based notification routine 800. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the Internet based notification routine 800. An Internet based notification routine is a server based application capable of processing transactions or requests and issuing  
20           notifications received from and sent to a plurality of COM device 100, a plurality of in-vehicle device 200, a plurality of Internet based data processing resources, or a plurality of servers.

25           In general, an Internet based notification routine effectuates the receiving and sending of notifications resultant from processing transaction and request information data communicated with a COM device 100, an in-vehicle device 200, an Internet appliance, or other data processing resource. Types of notifications can vary based in part on the transaction or request information, user

00602971.062300

preferences and settings, or notification server programming. Notification responses can be directed to a plurality of data processing resources. Such data processing resources can include wireless phones, pagers, PDA, PC 310, COM device 100, in-vehicle device 200, Internet appliance, Internet based servers, fax servers, e-mail servers, e-business servers, e-commerce servers, and other data processing resources.

In an exemplary embodiment an Internet based notification routine can be programmed with user specific information. Such user specific information can be a user's profile or other appropriate notification responses and destination information.

In this embodiment a transaction or request can include a request for a stock quote, headline news, or MP3 audio files. In addition, a transaction or request can result in notification of an event occurrence. Such a notification of an event occurrence can be sent to a person, a company, data processing device, an agency, or other network. An event occurrence can include an alarm condition or status, a vehicle mechanical problem or condition, a message or data waiting condition, or other type of event occurrence where notification is required or requested.

A transaction or request can include receiving an e-mail, e-business, or e-commerce transaction data communicated from an in-vehicle device 200, and subsequently fulfilling the transaction request by forwarding the transaction data to the appropriate destination. Furthermore, a transaction or request can include forwarding or notifying an in-vehicle device 200 that an e-mail, e-business, or e-commerce transaction is pending.

A transaction or request can include querying headline news or stock quotes based in part on user defined preferences. Likewise notification of new news or updated financial data pending can be performed by an Internet based notification routine. Processing begins in block 802.

5

In block 802 an in-vehicle device 200 data communicates between a COM device 100, a second in-vehicle device 200, an Internet appliance, and an Internet based server operating an Internet based notification routine. Such data communication can be in the form of a transaction or a request. In general, a transaction can be a task such as sending a fax, sending an e-mail, conducting e-business, performing e-commerce, sending notification to other data processing resources, or performing other task oriented events. Alternatively, a request can be for an Internet based notification routine to obtain data, change settings, upload or download data, or data communicate with other data processing resources. Processing then moves to block 804.

10

15

20

25

In block 804 the transaction or request is handled based in part on notification routine programming, and user specific settings or preferences. Transaction and request processing can invoke response data communications to other networks such as news networks, financial networks, specific web sites or portals, servers, databases, specific dot-com type of companies, police networks, law enforcement networks, national emergency agency 911 networks, other agency networks. In addition, transaction and request processing can invoke response data to fax servers, telecommunication servers, e-mail, e-business servers, e-commerce servers, or other servers and systems. The routine is then exited.

Referring to Figure 10 there is shown an Internet based information acquisition routine 900. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the Internet based information acquisition routine 900. An Internet based information acquisition routine allows a user or Internet server to initiate data communications with an in-vehicle device 200. Once data communication is established a user can select, or a server can data communicate online data for storage or viewing. Online data can include news, financial market information, e-mail, or other types of data. Processing begins in block 902.

In block 902 a user or an Internet server initiates data communication with an in-vehicle device 200. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 904.

In block 904 a user selects data stored locally to view or selects online data to download and or view. Alternatively, an Internet based server can download online based in part on user preferences or server settings. Processing then moves to block 906.

In an exemplary embodiment online data can include headline news such as CNN or FOX news. Online data can also include online new papers, financial data such as stock quotes, or online periodicals. A user can select and view data store locally in the in-vehicle device 200 or obtain online data via the Internet or other remote server.

5 In another exemplary embodiment an Internet server can independently without user intervention initiate delivery of online data. In this embodiment for example and not limitation an Internet server can be utilized to automatically download to an in-vehicle device 200 an online newspaper each morning or evening. A user can then read the paper on the way to work or during a commute.

10 In block 906 a user can select to download and store the data locally in the in-vehicle device 200. Data can then be retrieved and viewed at the user's convenience. User stored preferences within the in-vehicle device 200 or on an Internet based server can determine whether non-user initiated data communications from a server are stored locally at the in-vehicle device 200. Processing then moves to block 908.

15 In block 908 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

20 Referring to Figure 11 there is shown an Internet based command and control routine 1000. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the command and control routine 1000. An Internet based command and control routine allows  
25 a user or server to initiate data communication with an in-vehicle device 200 and direct the in-vehicle device 200 to perform certain command and control functions. Such command and control functions can include reporting GPS location data, enabling or disabling vehicle operation, changing system or engine

performance parameters, uploading or download data, reporting vehicle telemetry or metric information, activating alarm or security systems, or effectuating other command and control functions. Processing begins in block 1002.

5           In block 1002 a user or an Internet server initiates data communication with an in-vehicle device 200. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1004.

10           In block 1004 a user selects a command and control function or feature to be preformed at a remote in-vehicle device 200. The selection of a command and control function or feature can be initiated from a web browser, an in-vehicle device 200, or other PC or server based platform. The selected command and control functions are data communicated to the in-vehicle device 200. Processing then moves to block 1006.

15           In an exemplary embodiment a user or other appropriate agency can select command and control features and change preferences on an Internet based server. The server can then data communicate with the selected in-vehicle device 200 and effectuate the command and control request. The server can also receive a confirmation or status. A confirmation or status can include the information that the desired command and control functions have been executed or are pending execution.

20           In this type of embodiment for example and without limitation the police may decide to stop the operation of a vehicle equipped with an in-vehicle device



200. By initiating a data communication with an in-vehicle device 200 command and control function can be issued. Such command and control function could stop or disable the operation of a vehicle by way of for example and without limitation the ignition control interface 256.

5

In block 1006 the in-vehicle device 200 performs or activates the selected functions or features. Performing or activating selected functions or features can include enabling or disabling operation of a vehicle, opening or closing a microphone or video feed, activating or deactivating an alarm system, sending or receiving vehicle telemetry or metric data, or downloading MP3, video, advertising or other data. Processing then moves to block 1008.

10

In block 1008 confirmation of all executed command or control functions or feature are data communicated between the in-vehicle device 200, a COM device 100, an Internet based server, or an Internet appliance. Processing then moves to block 1010.

15

In block 1010 optionally data related to the placing of the command and control request, the data communication of such a request to an in-vehicle device 200, and the subsequent status and confirmation of the execution of such a request can be data processed. Data processing of the command and control related data can include saving such data in a database, or data communicating such data to a second server, the police, law enforcement, national emergency agency 911, a user, central monitoring station, or other appropriate agency. Processing then moves to block 1012.

20

25

In block 1012 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-

vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

5

Referring to Figure 12 there is shown an Internet based advertisement service routine 1100. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate the Internet based advertisement service routine 1100. An Internet based interactive digital content, and advertising routine can be used to serve coupon and advertising data to a plurality of in-vehicle device 200. Coupon and advertising data can be selected from a database of coupon and advertising data. The selection of such data can be based on a plurality of in-vehicle device 200 vehicle telemetry or metric data, user preferences, and server settings. In-vehicle device 200 data can include GPS location data as well as other vehicle operational data. Special promotions or offers, coupon data, and advertisement data can generally be referred to as promotional data. Advertisement, promotions, and other special offer content can be referred to as interactive digital content, or a plurality of interactive digital content. Processing begins in block 1102.

20

In block 1102 user preferences, server profiles and settings, promotional criteria, coupon data, advertising data, and other data can be entered into a database. Such a database can be an advertising server database. An advertising server database can be populated with data in a plurality of ways including by way of an in-vehicle device 200, a COM device 100, an Internet based server, a PC 310, an Internet appliance 322, or other database data management methods.

25

003290 T 4520960

In general, the advertising server can be populated with advertising data and hyperlinks to other advertising data at any time. The step in block 1102 of allowing the profile or promotional criteria to be changed can be optional. Allowing a user to change coupon and advertisement selection criteria can  
5 produce better coupon and advertisement serving results. For example and without limitation, if a user or occupant in a vehicle desired to locate restaurants geographically close to the vehicle then the user or occupant could set the advertising server criteria to produce coupons and advertising data related to geographically local restaurants. Processing then moves to block 1104.

10 In block 1104 a user or an Internet server initiates data communication with an in-vehicle device 200. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a  
15 COM device 100, or an Internet appliance 322. Processing then moves to block 1106.

In block 1106 a record set of coupon and advertising data based on the results of a query can be data communicated to the in-vehicle device 200. Query  
20 result can be based in part on vehicle telemetry or metric data, vehicle GPS location data, promotional criteria, user preferences, or other coupon and advertising selection criteria. Processing then moves to block 1108.

Certain promotional offers may require authorization for distribution prior  
25 to data communication and display of the coupon or advertisement data on an in-vehicle device 200. In block 1108 if required such an authorization can be performed. The authorization process can include sending notification to the promoting company or promoter, or basing authorization approval on statistical



In block 1114 as required charges are applied to the appropriate parties. The appropriate parties can include the advertiser, or the promoting company. In addition charges may be applied for fulfillment of the promotion or offer. Fulfillment of the promotion or offer can include printing coupons, delivery of data to the in-vehicle device 200, or other promotional fulfillment requirements. Processing then moves to block 1116.

In block 1116 as required updates to necessary databases are facilitated. Updates can include posting to user databases, posting to promotion databases for the purpose of keeping track of offers a user has received. In addition, statistical data related to an individual user, user responses, or other promotional statistics and metrics can be posted to the appropriate databases. Such databases can be Internet accessible and remotely locatable. The routine is then exited.

Referring to Figure 13 there is shown a routine 1200 for the selection of digital content based in part on GPS telemetry. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 1200. A selection of digital informational content based in part on GPS telemetry routine allows e-mail, electronic coupons, interactive advertising, road hazard warnings, maps, service information, or other e-business transactions and e-commerce transactions to be data communicated and transacted by way of an in-vehicle device 200. The selection of such data and transactions can be based in part on user preferences, server settings, vehicle telemetry or metrics, or GPS location data. Processing begins in block 1202.

In an exemplary embodiment an in-vehicle device 200 can data communicated GPS location data to an Internet based server. The Internet based server can consider user preferences, server settings and GPS location data when

selecting digital informational content. Digital informational content can be selected by querying a database of coupons, maps, service information, traffic condition databases, or advertisements. Upon identifying appropriate informational content an Internet based server can data communicate such informational content to the in-vehicle device 200 for viewing and interaction by the occupants of the vehicle.

In this embodiment informational content can be selected based in part on GPS location data. GPS location data can facilitate the selection of geographically relevant content. For example and without limitation, restaurant, collision repair center, service centers, entertainment, shopping, hotels, maps, hazard warnings, and other local businesses can choose to run coupon specials and advertisements in vehicles that may be moving through the area. Roadside businesses can run discount offers in a vehicle equipped with an in-vehicle device 200 as it moves down a freeway approaching the roadside business.

In another exemplary embodiment electronic maps, and road hazard warnings can be data communicated to an in-vehicle device 200. In such an embodiment map data and road hazard warning data can effectively inform the occupants of a vehicle of impending road conditions. In addition, map data and road hazard warning data can be utilized to determine alternative routines, and aid in reducing traffic delays.

In block 1202 data related to in-vehicle device 200, vehicle telemetry and metrics, and GPS location data is data communicated between an in-vehicle device 200 and an Internet based server. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data

communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1204.

5 In block 1204 the in-vehicle device 200 data communicates GPS location data to an Internet based server. In addition, the in-vehicle device 200 can execute any command and control functionality. Such command and control functionality can be effectuated in accordance with Figure 11, Internet based command and control routine 1000. Processing moves to block 1206.

10 In block 1206 an Internet based server or a computing resource accessible by way of an Internet based server queries a record set of data based in part on GPS location data communicated by the in-vehicle device 200. Results of a query can include restaurant, collision repair centers, service centers, entertainment, shopping, hotels, maps, hazard warnings, and other local business information  
15 preferable geographically relevant based on GPS location data. Processing then moves to block 1208.

20 In block 1208 a record set of data based on the results of the query can be data communicated to the in-vehicle device 200. Processing then moves to block 1210.

25 In block 1210 the in-vehicle device 200 can display the data as appropriate and interactively prompt the user as required. Displayed data can include coupon offers, advertisements, road hazard warnings, map data, service information, or other informational data. Processing then moves to block 1212.

In block 1212 confirmation of any executed command or control functions or feature are data communicated between the in-vehicle device 200, a COM







5 In block 1304 the in-vehicle device 200 data communicates GPS location data to an Internet based server. In addition, the in-vehicle device 200 can execute any command and control functionality. Such command and control functionality can be effectuated in accordance with Figure 11, Internet based command and control routine 1000. Processing moves to block 1306.

10 In block 1306 an Internet based server or a computing resource accessible by way of an Internet based server queries a record set of data based in part on GPS location data communicated by the in-vehicle device 200. Results of a query can include restaurant, collision repair centers, service centers, entertainment, shopping, hotels, maps, hazard warnings, and other local business information preferable geographically relevant based on GPS location data. Processing then moves to block 1308.

15 In block 1308 a record set of data based on the results of the query can be data communicated to the in-vehicle device 200. Processing then moves to block 1310.

20 If desired in block 1310 a user can program trip metrics or other trip parameters. Trip programming can occur at an in-vehicle device 200 or other data processing device such as a PC 310, a PDA 324, a wireless phone 312, or a pager 326. Trip planning data can reside within an in-vehicle device 200 or reside on an Internet based server or an Internet accessible database. Processing then moves to block 1312.

25 If desired in block 1312 a user can present data, update data, or redeem awards related to loyalty programs. A loyalty program can be a frequent traveling

program, or other points or miles type program. Processing then moves to block 1314.

5 In an exemplary embodiment an in-vehicle device 200 can data communicate with an Internet based server for the purpose of recording vehicle telemetry such as total miles driven. Promotional offers and other awards can be offered based on the total amount of accrued points or miles.

10 In block 1314 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

15 Processing in block 1316 begins an Internet based server routine. For effectuating Internet based vehicle tracking. The server side of the Internet based vehicle tracking routine handles data communication from a plurality of in-vehicle device 200.

20 In block 1316 a COM device 100, a second in-vehicle device 200, an Internet based server, or an Internet appliance initiates data communication with a specific in-vehicle device 200. Processing moves to block 1318.

25 In block 1318 the data communication between the specific in-vehicle device 200 and the Internet server can include vehicle telemetry data, vehicle metrics, GPS location data, and other related data. The received data communication from the in-vehicle device 200 can be handle in a plurality of

ways by the Internet based server. Handling data communications at the server can include processing the data, saving the data in a database, forwarding the data to a second server or database, updating a database, producing return data to the in-vehicle device 200, or otherwise processing, saving or data communicating with other data processing resources. Processing then moves to block 1320.

In block 1320 if desired data communication between the in-vehicle device 200 and the Internet based server can be logged. The routine is then exited.

Referring to Figure 15A and 15B there is shown a vehicle maintenance routine 1400. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate vehicle maintenance routine 1400. A vehicle maintenance routine allows an in-vehicle device 200 or a user to determine that the vehicle requires service. Once a service request is initiated a data communication to an Internet based server can locate if required the closest collision repair center, service center, or the availability of necessary replacement parts. In the case a service center or replacement parts are required a user can initiate scheduling of service at a collision repair center, service center, or scheduling of delivery if required replacement parts from the in-vehicle device 200.

In addition, map or other informational data related to the location of the collision repair center, service center, or location of replacement parts, or other service resources can be data communicated to the in-vehicle device 200. Processing begins in block 1402.

In block 1402 an in-vehicle device 200 monitors vehicle operational condition and engine performance. Processing then moves to decision block 1404.

5 In decision block 1404 a determination is made with respect to detecting vehicle or engine performance anomalies. If the resultant is in the affirmative, that is a vehicle or engine anomaly is detected then processing moves to block 1412. If the resultant is in the negative, that is a vehicle or engine anomaly is not detected then processing moves to decision block 1406.

10 In decision block 1406 a determination is made with respect to whether a user is requesting service. If the resultant is in the affirmative, that is a user is requesting service then processing moves to block 1412. If the resultant is in the negative, that is a user is not requesting service then the routine is exited.

15 In block 1412 data related to in-vehicle device 200, vehicle telemetry and metrics, and GPS location data is data communicated between an in-vehicle device 200 and an Internet based server. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to decision block 1414.

20 In decision block 1414 a determination is made with respect to whether a service center location is required. The determination can be based on user input, in-vehicle 200 programming, or server settings. If the resultant is in the affirmative, that is a service center location is required then processing moves to block 1418. If the resultant is in the negative, that is a service center location is not required then processing moves to decision block 1416.

25

5 In block 1418 an Internet based server having received data communication from the service requesting in-vehicle device 200 queries a list of suitable service center locations. Such a service center location list can be based in part on the type of service required, or the make or model of the vehicle, GPS location data, or other user preferences or server settings.

10 The list of suitable service location can be data communicated to the in-vehicle device 200 requesting service. Data communications between an Internet based server and the in-vehicle device 200 requesting service can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1420.

15 In block 1420 a user can select from the list of suitable service center locations a specific service center in which to obtain vehicle service. Processing then moves to decision block 1416.

20 In decision block 1416 a determination is made with respect to whether part(s) are required to effectuate the repair. If the resultant is in the affirmative, that is part(s) are required to effectuate the repair then processing moves to block 1408. If the resultant is in the negative or the resultant can not be determined with the available information processing then moves to block 1410.

25 In block 1408 the user can select to have the repair part(s) ordered or delivered to the service location. The ordering of part(s) can be directly from the service center, from a local auto parts store, or from an online store such as PARTS.COM, WRENCHHEAD.COM, SPORTWING.COM, CARPARTSONSALE.COM, CARPARTS.COM, NAPAONLINE.COM,

PARTSAMERICA.COM, CSKAUTO.COM, ALLDATA.COM, MECHANICNET.COM, other part suppliers, or from other part databases. Processing then moves to block 1410.

5           In block 1410 if required a service request or part(s) request can be data communicated between the Internet based server and the requesting in-vehicle device 200. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM  
10           device 100, or an Internet appliance 322. Processing then moves to block 1422.

          In block 1422 the Internet based server or Internet application server having received the service or part(s) request places the order as required. Placing the orders can include scheduling service with the appropriate service center, and  
15           ordering or scheduling the delivery of repair part(s) to effectuate the repair. Service and parts ordering can be by way of e-business or e-commerce transactions online or by way of intervention of a customer service or help desk support center. Processing then moves to block 1424.

20           In block 1424 confirmation that the Internet based server has received the service or part(s) request and subsequently has placed the appropriate orders can be data communicated to the in-vehicle device 200 requesting confirmation. Processing then moves to block 1426.

25           In block 1426 if desired by the user an electronic map or driving directions on how to get to the service center or repair part pick-up location can be data communicated to the service requesting in-vehicle device 200. Such data can be displayed or printed as required by the user. Processing then moves to block 1428.

In block 1428 the Internet based server or Internet application server can bill as appropriate the parties involved in the service request transaction. The appropriate parties and schedule of billing fees can include licensing fees, royalties, fees for coordinating and identifying the service center location, fees for scheduling the service request, fees for identifying replacement part(s) and replacement parts location, and or fees coordinating replacement part(s) delivery. In addition, a schedule of billing charges can include a percentage of the service center charge, a percentage of the repair cost, a percentage of the repair part cost, or for serving map and other informational data. A user can be billed by way of credit card, or through in-vehicle device 200 network service contract arrangement, or through other appropriate billing arrangements. Processing then moves to block 1430.

In block 1430 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

Referring to Figure 16 there is shown an e-mail, facsimile, and personal data assistant communication (PDA) routine 1500. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 1500. An e-mail, facsimile, and personal data assistant (PDA) communication routine can effectuate the sending and receiving of e-mail, facsimile, and PDA data between an in-vehicle device 200 and an Internet based data processing resource. Processing begins in block 1502.



5 In block 1502 a user or an Internet server initiates data communication with an in-vehicle device 200. Data communication between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1504.

10 In block 1504 an Internet based server or Internet application server can data communicate with the in-vehicle device 200 desiring to send an e-mail, facsimile, or PDA data. E-mail, facsimile data, PDA data, or other data can be data communicated between the in-vehicle device 200 and the Internet server or Internet application server. If required or desired e-mail, facsimile data, PDA data, and other data can be printed. Processing then moves to block 1506.

15 In block 1506 an Internet based server or Internet application server can as required query a database, obtain user preferences, access a remote data location, or data communicate with a data communicating piece of equipment. A data communicating piece of equipment can include a server, PDA, phone, Internet appliance, a COM device 100, a specific in-vehicle device 200. If required or  
20 desired e-mail, facsimile data, PDA data, and other data can be printed. Processing then moves to decision block 1508.

25 In decision block 1508 a determination is made as to whether the Internet server, or Internet application server needs to be configured as a gateway or router. If the resultant is in the affirmative, that is the Internet server, or Internet application server needs to be configured as a gateway or router then processing moves to block 1510. If the resultant is in the negative, that is the Internet server,

or Internet application server does not need to be configured as a gateway or router then the routine is exited.

5 In an exemplary embodiment when an e-mail server destination, facsimile data destination, PDA data destination, or other data destination can not be directly reached an Internet server or Internet application server can receive and cache the data transmission or in real time redirect the data transmission. The Internet server or Internet application server can also be configured as a gateway or router to a second server or second network system. The second server or  
10 second network system can contain the data destination. In such as embodiment the Internet server or Internet application server can be configured as a gateway or router and redirect the data transmission to a second Internet server or Internet application server. Delivery of the data to the intended data destination can be effectuated by a second server or Internet application server.

15 In block 1510 the Internet server or Internet application server can be configured to as a gateway or router to a second server or second network system. Processing then moves to block 1512.

20 In block 1512 a second server or a second Internet application server can data communicate with the in-vehicle device 200 desiring to send and receive e-mail, facsimile, or PDA data. E-mail, facsimile data, PDA data, or other data can be data communicated between the in-vehicle device 200 and the Internet server or Internet application server. If required or desired e-mail, facsimile data, PDA  
25 data, and other data can be printed. Processing then moves to block 1514.

In block 1514 a second server or a second Internet application server can as required query a database, obtain user preferences, access a remote data

location, or data communicate with a data communicating piece of equipment. A data communicating piece of equipment can include a server, PDA, phone, Internet appliance, a COM device 100, or a specific in-vehicle device 200. If required or desired e-mail, facsimile data, PDA data, and other data can be  
5 printed. Processing then moves to decision block 1516.

In block 1516 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data  
10 communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

Referring to Figure 17 there is shown an Internet based remote vehicle diagnostic routine 1600. An Internet based remote vehicle diagnostic routine can be utilized to remotely analyze vehicle engine performance. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate a remote vehicle diagnostic routine 1600. Processing begins  
15 in block 1602.

In an exemplary embodiment a remote mechanic can by way of a data communication between an in-vehicle device 200 and an Internet data processing resource monitor and analyze vehicle engine performance. In addition, certain remote adjustments can be made by data communicating such adjustment requests  
20 to the in-vehicle device 200. As required the in-vehicle device 200 can by way of the interface to the vehicle engine control system 210 data communicate or effectuate the requested adjustments.

In block 1602 a user or an Internet server initiates data communication with an in-vehicle device 200. Data communication between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1604.

In block 1604 an in-vehicle device 200 data communicate engine data, vehicle telemetry and metric data, or original equipment manufacture (OEM) control system data. In addition, data from the in-vehicle device 200 can include status, conditions, or other data. Processing then moves to block 1606.

In block 1606 data received at the Internet based server can be viewed, monitored, recorded, or otherwise be utilized to analyze the operation of the vehicle interconnected with the specific in-vehicle device 200. Data received can include engine data, vehicle telemetry and metric data, or OEM vehicle control system data. In addition, data from the in-vehicle device 200 can include status, conditions, or other data. Processing then moves to block 1608.

In block 1608 if required or desired certain adjustable parameters within or accessible by the in-vehicle device 200, or within the OEM vehicle control system can be adjusted. Adjustable parameters can include fuel mixture, engine settings, idle RPM, and other in-vehicle device 200, or vehicle engine adjustable parameters. Processing then moves to block 1610.

In block 1610 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data

communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

5                   Referring to Figure 18 there is shown an Internet based audio and video server routine 1700. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 1700. An Internet based audio and video server routine allows a user to select music and video. Music and video can be selected at an in-vehicle device 200. A menu  
10                   system can allow a user to selectively download or stream the audio and video data for storage or playback. Radio data, audio data, and video data can be referred to a digital content, or a plurality of digital content. Processing begins in block 1702.

15                   In block 1702 a user initiates the in-vehicle device 200 radio, audio, or video menu feature. Such a feature allows a user to select radio, audio, or video programming to selectively download, store, or playback. Processing then moves to block 1704.

20                   In block 1704 data communication between an Internet based server and an in-vehicle device 200 can be initiated. Data communication between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance  
25                   322. Processing then moves to block 1706.

5            In block 1708 a user can alter the play list or settings. Altering the play list or settings can include adding, deleting, sorting, or otherwise changing the parameters, features, or content of the play list. Processing then moves to block 1710.

15 In block 1712 if desired a user's radio, music, or video selections can be downloaded and saved locally within an in-vehicle device 200. Alternatively, a user's selection can be streamed from the Internet for playback, and optionally saved (while being streamed) within an in-vehicle device 200. Processing then  
20 moves to decision block 1714.

25 In decision block 1714 a determination is made as to whether a user's selections will be played by way of the in-vehicle device 200 sound system or by way of the vehicle's sound system. If the resultant is in the affirmative, that is a user selects to have the playback sent to the vehicle's sound system then processing moves to block 1716. If the resultant is in the negative, that is the user selects to have the playback sent to the in-vehicle device 200 sound system then processing moves to block 1718.

In block 1716 the user's selections can be played by way of the vehicle's sound system. Radio, music, video, or other data can be communicated to the vehicle's sound system by way of the vehicle radio interface 248. Processing then moves to block 1720.

In block 1718 the user's selections can be played by way of the in-vehicle device 200 sound system. Processing then moves to block 1720.

In block 1720 if desired or required billing, fees, or other charges can be applied to the appropriate party's including the user, or advertisers for the service, royalties, download, or for other appropriate reasons. A user can be billed by way of credit card, or through in-vehicle device 200 network service contract arrangement, or through other appropriate billing arrangements. Processing then moves to block 1722.

In block 1722 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

Referring to Figure 19 there is shown an Internet based audio and videoconferencing routine 1800. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 1800. An Internet based audio and videoconferencing routine 1800 allows a user to conduct audio and videoconferencing by way of a plurality of in-vehicle

device 200 and a plurality of other data processing resources. Processing begins in block 1802.

5 In block 1802 a user initiates the in-vehicle device 200 audio conferencing or videoconferencing menu feature. Such a feature allows a user to initiate and conduct audio conferencing and or videoconferencing between an in-vehicle device 200 and a plurality of other data processing resources. A plurality of other data processing resources can include a plurality of in-vehicle device 200, an Internet based server, an Internet based application server, a COM device 100, or an Internet appliance. In addition, a plurality of data processing resources can include, a wireless phone, a PDA, a pager, a PC 310, and other types and styles of data processing resources Internet or non-Internet based. Processing then moves to block 1804.

10 In block 1804 data communication between an Internet based server and an in-vehicle device 200 can be initiated. Data communication between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 1806.

15 In block 1806 a personalized user conference list and settings can be fetched and displayed from an Internet based server, or fetched from local profile data within an in-vehicle device 200. Processing then moves to block 1808.

20 In block 1808 a user can alter the conference list or settings. Altering the conference list or settings can include adding, deleting, sorting, or otherwise



changing the parameters, features, or content of the conference list. Processing then moves to block 1810.

5 In block 1810 any alterations to a user's profile, features, parameters, settings, or conference list can be saved. Saving can include saving the user's profile, features, parameters, settings, or conference list on an Internet based server, or saving the user's profile, features, parameters, settings, or conference list within an in-vehicle device 200. Processing then moves to decision block 1812.

10 In decision block 1812 a determination is made as to whether a user's audio or videoconference (audio portion of videoconference) will be played by way of the in-vehicle device 200 sound system or by way of the vehicle's sound system. If the resultant is in the affirmative, that is a user selects to have the  
15 playback sent to the vehicle's sound system then processing moves to block 1814. If the resultant is in the negative, that is the user selects to have the playback sent to the in-vehicle device 200 sound system then processing moves to block 1816.

20 In block 1814 the user's audio or video (audio portion of videoconference) can be played by way of the vehicle's sound system. Audio conference or (audio portion of videoconference) conference, or other data can be communicated to the vehicle's sound system by way of the vehicle radio interface 248. Processing then moves to block 1816.

25 In block 1816 the user's selections can be played by way of the in-vehicle device 200 sound system. Processing then moves to block 1818.

5 In block 1818 if desired or required billing, fees, or other charges can be applied to the appropriate party's including the user, or advertisers for the service, royalties, download, or for other appropriate reasons. A user can be billed by way of credit card, or through in-vehicle device 200 network service contract arrangement, or through other appropriate billing arrangements. Processing then moves to block 1818.

10 In block 1820 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

15 Referring to Figure 20 there is shown an online part ordering and delivery routine 1900. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 1900. An online part ordering and delivery routine allows a user to initiate a part order and arrange for part delivery by utilizing a web browser, a COM device 100, an in-vehicle device 200, an Internet based server, or an Internet appliance.

20 In an exemplary embodiment a store display can include a COM device 100. A customer can interact with the COM device 100 querying product information and accessing other types of digital content. A customer can utilize the COM device 100 to research product information, or identify the correct product and then make the physical selection from the store product display. In the event a product is not physically available or the customer desires to transact an e-commerce or e-business such a transaction can be performed by the customer

at the COM device 100. A customer can interact with the COM device 100, such interaction can include transferring data between the COM device 100 and a wireless device, or a programmable device. In addition a customer can interact with a COM device 100 manually, including interaction through voice  
5 recognition, biometric recognition, a keypad, general purpose COM device 100 input or output, or touch screen input. In-vehicle device 200 data can be data communicated to the COM device 100 to aid in the digital content selection for the customer. Processing begins in block 1902.

10 In block 1902 a user by way of a web browser, a COM device 100, an in-vehicle device 200, an Internet based server, or an Internet appliance. Can initiate an e-commerce or e-business transaction. Such an e-commerce or e-business transaction can include searching for a part or information, identifying a part, researching parts, ordering parts, buying parts, or arranging for shipping or  
15 delivery parts or information. Processing then moves to block 1904.

In block 1904 a user can search for part(s) information, identify part(s), research part(s), or select part(s). Processing then moves to block 1906.

20 In block 1906 if desired a user can check inventory of the selected parts. Processing then moves to block 1908.

In block 1908 a user can select the preferred part(s) delivery method. Such part(s) delivery methods can include traditional shipping methods, courier  
25 services, or other part delivery methods. In addition, a user can arrange to pick-up the part from a part pick-up location. Processing then moves to decision block 1910.

In decision block 1910 a determination is made whether the user wants the selected part(s) delivered. If the resultant is in the affirmative, that is the user wants the selected part(s) delivered then processing moves to block 1914. If the resultant is in the negative, that is the user does not want the selected part(s) delivered then processing moves to decision block 1912.

In block 1914 a user is allowed to enter delivery information including a delivery address, and or other types of delivery information. Processing then moves to block 1922.

In decision block 1912 a determination is made whether the user wants the selected part(s) shipped. If the resultant is in the affirmative, that is the user wants the selected part(s) shipped then processing moves to block 1916. If the resultant is in the negative, that is the user does not want the selected part(s) shipped then processing moves to decision block 1918.

In block 1916 a user is allowed to enter shipping information including a shipping address, shipping method, and or other types of shipping information. Processing then moves to block 1922.

In block 1918 a user can query a database of part pick-up information. Part pick-up information can include part pick-up locations, and other part pick-up information. Processing then moves to block 1920.

In block 1920 a user can select a preferred location to pick-up parts from a list of part pick-up locations queried in block 1920. Processing then moves to block 1924.

In block 1922 a database of suitable delivery information can be queried. Queried information can include delivery location, and other type of delivery information. Processing then moves to block 1924.

5 In block 1924 information obtained from a pick-up location query, or a delivery location query can be data communicated to an in-vehicle device 200 requesting such information. The in-vehicle device 200 can display the information and can allow the user to respond. Processing then moves to decision block 1926.

10 In decision block 1926 a determination is made whether a user by way of an in-vehicle device 200 accepts purchase terms, conditions, and delivery or shipping schedule terms. If the resultant is in the affirmative, that is the user affirmatively accepts the terms and conditions then processing moves to block 15 1928. If the resultant is in the negative, that is the user does not affirmatively accept the term and conditions then processing moves to block 1904.

20 In block 1928 the e-commerce or e-business transaction is completed and an order with the appropriate part procurement location(s), appropriate part pick-up location(s), and or appropriate part delivery location(s). Processing then moves to block 1930.

25 In block 1930 a confirmation that the e-commerce or e-business transaction has been ordered and is complete can be data communicated to the requesting in-vehicle device 200. In addition, a sales or order confirmation can also be data communicated to the requesting in-vehicle device 200, stored in a database, or otherwise data processed. Processing then moves to block 1932.

In block 1932 as required the user, e-commerce fulfillment agency, part(s) location, delivery service, and or other appropriate agencies can be billed or credited. A user can be billed by way of credit card, or through in-vehicle device 200 network service contract arrangement, or through other appropriate billing arrangements. The routine is then exited.

Referring to Figure 21 there is shown a biometric authorization routine 2000. COM device 100, in-vehicle device 200, and various data processing resources cooperate together as a system to effectuate routine 2000. A biometric authorization routine requires a user to present valid biometric input to be authorized before operation of the vehicle and systems in the vehicle are enabled for use. Biometric input can include palm, hand, finger, eye (iris scan), voice and voice commands, or other biometric input data. Processing begins in block 2002.

In block 2002 a user presents biometric input. Biometric input can be present by way of the biometric input interface 280. Processing then moves to block 2004.

In block 2004 the biometric input is authorized or otherwise validated locally or remotely. If remote authorization or validation is desired, the biometric input can be data communicated between an Internet based server and the in-vehicle device 200. Data communications between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to decision block 2006.

In block 2006 a determination is made as to whether the biometric input presented by the user is approved or valid. If the resultant is in the affirmative,

that is the biometric input presented is approved and or validated then processing moves to block 2010. If the resultant is in the negative, that is the biometric input presented is not approved and or validated then processing moves to block 2008. Approval or validity results can be data communicated from an Internet based server if required.

In block 2008 the user can be prompted that the biometric input has been denied or is invalid. Processing then moves to block 2012.

In block 2010 by way of the in-vehicle device 200 the vehicle and the system associated with the vehicle are enable for use. Processing then move to block 2014.

In block 2014 if desired or required an in-vehicle device 200 can data communicate engine data, vehicle telemetry and metric data, states, original equipment manufacture (OEM) control system data, or other vehicle data. In addition, data from the in-vehicle device 200 can include status, conditions, or other data. Processing then moves to block 2012.

In block 2012 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

Referring to Figure 22 there is shown a vehicle tracking and location routine 2100. COM device 100, in-vehicle device 200, and various data

processing resources cooperate together as a system to effectuate routine 2100. A vehicle tracking and location routine 2100 effectuates an Internet based method of tracking a vehicle for the purpose of regulating vehicle and vehicle occupant attendance based on vehicle entry to and exit from a parking area through a parking gate or parking terminal. In addition, a routine 2100 also effectuates the ability to enable or disable operation of a vehicle when the vehicle (equipped with an in-vehicle device 200) passes in wireless proximity to a COM device 100.

Furthermore, routine 2100 effectuates vehicle route or trip progress tracking, and enables the calculating of the vehicle's rate of speed between checkpoints equipped with COM device 100. In an exemplary embodiment for example and not limitation, a vehicle's rate of speed can be utilized for the purpose of identifying speeders and issuing speeding tickets. Processing begins in block 2102.

In block 2102 data communication between an Internet based server and an in-vehicle device 200 can be initiated. Data communication between an Internet based server and an in-vehicle device 200 can be a direct data communication between the server and the in-vehicle device 200 or a data communication facilitated by way of a COM device 100, or an Internet appliance 322. Processing then moves to block 2104.

In block 2104 the in-vehicle device 200 data communicates GPS location data to an Internet based server. In addition, the in-vehicle device 200 can execute any command and control functionality. Such command and control functionality can be effectuated in accordance with Figure 11, Internet based command and control routine 1000. Processing moves to block 2106.



5 In block 2106 a vehicle location database is modified. In an exemplary embodiment a vehicle location database can be utilized to track the location of a vehicle at certain checkpoints equipped with a COM device 100. Checkpoint can include entrances and exits to parking areas, points to calculate vehicle speed, as well as other applications requiring checkpoint verification of a vehicle's location. Processing then moves to block 2108.

10 In block 2108 data from an Internet based resource can be sent to the initiating COM device 100, or in-vehicle device 200. Such return data can include an acknowledgement of vehicle location database update complete, command and control functions, interactive digital content, as well as other appropriate return data. Processing then moves to block 2110.

15 In block 2110 data communication can be optionally suspended or terminated between a COM device 100, an in-vehicle device 200, a specific in-vehicle device 200, an Internet based server, or an Internet appliance. Data communication suspension or termination can be desirable where the cost of communications, the availability of communications, or the option not to maintain data communications is desirable. The routine is then exited.

20 While this invention has been described with reference to specific embodiments, it is not necessarily limited thereto. Accordingly, the appended claims should be construed to encompass not only those forms and embodiments of the invention specifically described above, but to such other forms and  
25 embodiments, as may be devised by those skilled in the art without departing from its true spirit and scope.

[illegible]

- [illegible]

27

28 wherein, said in-vehicle device wirelessly data communicates, by way of said  
29 communication interface device, with said plurality of global network based  
30 data processing resources.

31

1 2. The network system in accordance with claim 1 wherein, said communication  
2 interface device further comprises a wireless data connection for perfecting a  
3 network connection with a wireless device.

4

1 3. The network system in accordance with claim 2 wherein, said wireless data  
2 connection includes at least one of the following: a wireless transceiver  
3 interface, said wireless device interface, a wireless modem interface, a  
4 wireless phone interface, or a wireless data link.

5

1 4. The network system in accordance with claim 2 wherein, said wireless device  
2 is at least one of the following: a wireless phone, a personal data assistant, a  
3 pager, a pocket sized personal computer, an internet appliance, or a  
4 programmable storage device.

5

1 5. The network system in accordance with claim 1 wherein, said in-vehicle  
2 device further comprises a wireless data connection for perfecting a network  
3 connection with a wireless device.

4

1 6. The network system in accordance with claim 5 wherein, said wireless data  
2 connection includes at least one of the following: a wireless transceiver  
3 interface, said wireless device interface, a wireless modem interface, a  
4 wireless phone interface, or a wireless data link.

5

002290" T 2629960

- 2 7. The network system in accordance with claim 5 wherein, said wireless device  
3 is at least one of the following: a wireless phone, a personal data assistant, a  
4 pager, a pocket sized personal computer, an internet appliance, or a  
5 programmable storage device.  
6
- 1 8. The communication interface device in accordance with claim 1 wherein, said  
2 plurality of communication interfaces includes at least one of the following  
3 communication interface types: a universal serial bus port, a personal data  
4 assistant interface, an RS232 interface, an RS485 interface, a carrier current  
5 interface, a network connection to the Internet, a modem interface, a wireless  
6 modem interface, a wireless phone transceiver, a wireless phone interface, a  
7 wireless data link, or a local area network interface.  
8
- 1 9. The network system in accordance with claim 1 wherein, said communication  
2 interface device is at least one of the following: a personal computer, an  
3 internet appliance, a network router, a network concentrator, a network hub, a  
4 network server, or a network gateway.  
5
- 1 10. The network system in accordance with claim 1 wherein, said plurality of  
2 global network based data processing resources include at least one of the  
3 following: a global network server, a global network application server, a  
4 global network database, a virtual private network, an emergency monitoring  
5 network, a second communication interface device, a second in-vehicle  
6 device, a personal computer, a wireless phone, a personal data assistant, a  
7 pager, a pocket sized personal computer, a programmable storage device, or  
8 an internet appliance.  
9
- 1 11. The network system in accordance with claim 1 wherein, said plurality of  
2 communication means data communicates by at least one of the following

connectivity standards or protocol: a wired connection, a personal data assistant interface, a wireless phone interface, an RS232 serial interface, an RS485 interface, a USB port interface, an ethernet connection, a TCP/IP type network connection, a PPP type network connection, a SLIP type network connection, a socket layer network connection, BLUETOOTH protocol or standard, or WIRELESS APPLICATION PROTOCOL or standard.

12. The network system in accordance with claim 1 wherein, said communication interface device is physically located at a store display accessible by a customer.

13. A global network based data processing system for receiving informational, operational, telemetry, or metric data from a vehicle, and for allowing a user to access and compile result data from a plurality of databases for the purpose of identifying, procuring, or transacting electronic commerce related to vehicle service, vehicle maintenance, or vehicle replacement parts comprising:

a communication interface device for receiving said user input, and for receiving said vehicle informational, operational, telemetry, or metric data; and

a plurality of global network based data processing resources, said plurality of global network based data processing resources data communicate with said communication interface device;

wherein, said plurality of global network based data processing resources data communicate with said communication interface device for purposes including: obtaining said user input, providing result data to said user, receiving, processing, or selectively storing said vehicle informational,

19. A networking method for delivering a plurality of digital content to a data processing device, said data processing device being an in-vehicle device

installed in a vehicle, or a communication interface device, or a personal computer, or a wireless device,

wherein, said personal computer is interconnected with said communication interface device, and said wireless device has data communication access to either of said in-vehicle device or said communication interface device comprising:

a) communicating said plurality of digital content wirelessly between said in-vehicle device, said communication interface device, or said wireless device;

b) routing said plurality of digital content to first to said communication interface device then from said communication interface device to at least one of a plurality of global network based data processing resources;

c) receiving said plurality of digital content at said plurality of global network based data processing resources;

d) determining return said plurality of digital content; and

e) routing return said plurality of digital content to first to said communication interface device then selectively from said communication interface device to at least one of the following data destinations: said in-vehicle device, or a second communication interface device, or said personal computer, or said wireless device;

20. The networking method in accordance with claim 19 wherein, said wireless device is at least one of the following: a wireless phone, a personal data







**ABSTRACT**

An in-vehicle device data communicates with Internet based data processing resources for the purpose of transacting e-mail, e-commerce, and e-business. The in-vehicle device and the Internet based data processing resources can effectuate a wide variety of e-mail, e-commerce, and e-business including accessing auto part databases, warranty, customer, and other remote databases. In addition, e-mail, e-commerce, and e-business transactions can include vehicle security and vehicle service management, data communicating Internet based radio, audio, MP3, MPEG, video, and other types of data. Furthermore, e-mail, e-commerce, and e-business transactions can include interactive advertising, promotional offers, coupons, and supporting other remote data communications.

The in-vehicle device can also include functionality for remote monitoring of vehicle performance, data communicating and accessing remote Internet based content and data, and effectuating adjustments and control of vehicle operation. Remote monitoring and control of vehicle operation can be by way of an Internet based data processing resource and can include engine control system programming and setting adjustment, vehicle monitoring, and transmission of vehicle telemetry and metric data. Vehicle telemetry and metric data can include global positioning system (GPS) data, vehicle operational data, engine performance data, and other vehicle data.

The in-vehicle device can also wirelessly data communicate with a communication interface device (COM device) or an Internet appliance. Such COM devices or Internet appliances can data communicate wirelessly with an in-vehicle device and simultaneously data communicate in a wired or wireless mode of operation to Internet based data processing resources, and to other data processing resources.






Fig. 1C




Fig. 1D




Fig. 1E




Fig. 1F




Fig. 1G




Fig. 1H




Fig. 1I




Fig. 1J




Fig. 1K




Fig. 1L








1






**Fig. 2B**

The diagram illustrates a network architecture centered around the Internet (362). Various devices and networks are connected to the Internet cloud:

- COM Devices:** Multiple COM Devices (100) are shown, including 100N, 100P, 100Q, 100R, and 100S. Some are connected to each other (e.g., 100P and 100Q) and to the Internet cloud (e.g., 100S).
- PCs:** PCs (310B, 310C, 310D) are connected to the Internet cloud. PC 310D is also connected to a Hub/Concentrator (338B).
- Hub/Concentrator:** Two Hub/Concentrators (338A, 338B) are shown. 338B is connected to PC 310D and a Router/Gateway (340). 338A is connected to PC 310C and the Router/Gateway (340).
- Router/Gateway:** A Router/Gateway (340) is connected to the Internet cloud and the Hub/Concentrators (338A, 338B).
- Emergency Monitoring Network:** An Emergency Monitoring Network (332) is connected to the Internet cloud and a Virtual Private Network (334).
- Virtual Private Network:** A Virtual Private Network (334) is connected to the Internet cloud and the Emergency Monitoring Network (332).
- User/Personal PC/Network:** A User/Personal PC/Network (336) is connected to the Internet cloud.
- Internet Appliance:** An Internet Appliance (322D) is connected to the Internet cloud.
- Internet Server and Application Server:** An Internet Server (364) and an Internet Application Server (358) are connected to the Internet cloud. The Internet Server (364) is also connected to a database (356A). The Internet Application Server (358) is connected to a database (356B).

**Fig. 2C**



**100**  
**Fig. 3**










**600**  
**Fig. 7**

**700**  
**Fig. 8A**

```

graph TD
    E((E)) --> 718[Vehicle Reports Current GPS Positioning And Executes Desired Command And Control Functionality, Including Stopping The Engine]
    718 --> 720[Confirmation Of Executed Command And Control Functions (i.e. Success And Failure) Is Data Communicated Between A COM Device 100, An In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance]
    720 --> 722[Optionally Data Communication Between A COM Device 100, An In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance Can Be Suspended Or Terminated]
    722 --> Exit([Exit])

```



**700**  
**Fig. 8B**

```
graph TD; Start([Start]) --> 802[An In-Vehicle Device 200 Data Communicates Between A COM Device 100, A Second In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance]; 802 --> 804[Based In Part On User Or Agency Preference Settings Or Database Settings Notification Of Data Communication And Or Responses To Data Communications Can Be Data Communicated With A COM Device 100, An In-Vehicle Device 200, An Internet Server, An Internet Appliance, Police, User, or An Appropriate Agency]; 804 --> Exit([Exit]);
```

Start

802

An In-Vehicle Device 200 Data Communicates Between A COM Device 100, A Second In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance

804

Based In Part On User Or Agency Preference Settings Or Database Settings Notification Of Data Communication And Or Responses To Data Communications Can Be Data Communicated With A COM Device 100, An In-Vehicle Device 200, An Internet Server, An Internet Appliance, Police, User, or An Appropriate Agency

Exit

```
graph TD; Start([Start]) --> 902[A User Or Internet Server Initiates Data Communication Between A COM Device 100 And An In-Vehicle Device 200]; 902 --> 904[A User Can Select Or An Internet Based Server Can Serve News, Financial Market, Other Headline Or Online Data To View]; 904 --> 906[A User Can Select To Download The Data Selected To Be Stored Locally At An In-Vehicle Device 200]; 906 --> 908[Optionally Data Communication Between A COM Device 100, In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance Can Be Suspended Or Terminated]; 908 --> Exit([Exit]);
```

Flowchart 900 illustrates a method for data communication between a COM device and an in-vehicle device. The process begins with a **Start** terminal, leading to step 902: **A User Or Internet Server Initiates Data Communication Between A COM Device 100 And An In-Vehicle Device 200**. This is followed by step 904: **A User Can Select Or An Internet Based Server Can Serve News, Financial Market, Other Headline Or Online Data To View**. Step 906: **A User Can Select To Download The Data Selected To Be Stored Locally At An In-Vehicle Device 200** follows. Step 908: **Optionally Data Communication Between A COM Device 100, In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance Can Be Suspended Or Terminated** is the final process step. The flowchart concludes at an **Exit** terminal.

**900**  
**Fig. 10**


```


graph TD
    Start([Start]) --> 1002[A User Or Internet Server Initiates Data Communication Between A COM Device 100, An In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance]
    1002 --> 1004[User Selects Function(s), or Feature(s) Associated With The In-Vehicle Device 200 And Or Function(s) Or Feature(s) Accessible By Way Of An In-Vehicle Device 200]
    1004 --> 1006[In-Vehicle Device 200 Performs Or Activates The Selected Function(s) Or Feature(s)]
    1006 --> 1008[Confirmation Of Executed Command And Control Function(s) Or Feature(s) (i.e. Success And Failure) Is Data Communicated Between COM Device 100, In-Vehicle Device 200, An Internet Based Server, Or Internet Appliance]
    1006 --> 1010[Based In Part On Agency Or User Preference Settings Notification Can Be Saved In A Database And Or Data Communicated To A Second Server, The Police, User, or An Appropriate Agency]
    1008 --> 1004
    1010 --> 1012[Optionally Data Communication Between A COM Device 100, An In-Vehicle Device 200, An Internet Based Server, Or An Internet Appliance Can Be Suspended Or Terminated]
    1012 --> Exit([Exit])
  
```

**1000**


**Fig. 11**

**Fig. 11**






**1200**  
**Fig. 13**





**1300**  
**Fig. 14**






**1400**  
**Fig. 15A**







**1500**  
**Fig. 16**




**1600**  
**Fig. 17**




**1700**  
**Fig. 18**






**Fig. 20**  
**1900**



**2000**  
**Fig. 21**





**2100**  
**Fig. 22**

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00 OMB 0651-0032  
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)</b>  <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing      OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Attorney Docket Number</b>	BK-020-04
	<b>First Named Inventor</b>	H. Brock Kolls
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	
	<b>Filing Date</b>	June 23, 2000
	<b>Group Art Unit</b>	
	<b>Examiner Name</b>	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**An Internet Based Network For Automotive Applications Including The Facilitation Of E-Commerce And E-Business, And Management Of Wireless Connectivity With Vehicles**

the specification of which (Title of the Invention)

☒ is attached hereto  
OR  
☐ was filed on (MM/DD/YYYY) [ ] as United States Application Number or PCT International

Application Number [ ] and was amended on (MM/DD/YYYY) [ ] (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below

Application Number(s)	Filing Date (MM/DD/YYYY)	
		<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00 OMB 0651-0032  
Patent and Trademark Office, U S DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

## DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application

U. S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer  
Number Bar Code  
Label here


Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto

Direct all correspondence to: ☐ Customer Number or Bar Code Label ☐ OR ☒ Correspondence address below

Name	H. Brock Kolls				
Address	1573 Potter Drive				
Address					
City	Pottstown	State	PA	ZIP	19464
Country	USA	Telephone	610-705-3371	Fax	610-705-3371

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any])			Family Name or Surname				
H. Brock			Kolls				
Inventor's Signature					Date	6/23/00	
Residence City	Pottstown	State	PA	Country	USA	Citizenship	USA
Post Office Address	1573 Potter Drive						
Post Office Address							
City	Pottstown	State	PA	ZIP	19464	Country	USA

☐ Additional inventors are being named on the \_\_\_\_\_ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto